SOLANTO MULTI Z 600MM 2550-4500LM 830 IP20 I CL. OPAL WHITE 30-53W

DETAILED CARD





TECHNICAL PARAMETERS

Light source: LED module

Rated power [W] - range: 30/38/45/53

Colour temperature [K]: 3000

Luminous flux of the luminaire [lm] -

range:

2550/3200/3800/4500

Ingress protection: IP20

Electrical protection class:

Diffuser material: PS

Diffuser type: OPAL

Colour of the body: white

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.



SOLANTO MULTI Z 600MM 2550-4500LM 830 IP20 I CL. OPAL WHITE 30-53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463075
EAN:	5905963463075
Light source:	LED module
Rated power [W] - range:	30/38/45/53
Luminous flux of the luminaire [lm] - range:	2550/3200/3800/4500
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	85
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	112000
LED lifespan L80B20 [h]:	70 000

LED lifespan L90B10 [h]:	34000
Diffuser material:	PS
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	white
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	ø602/32
Ingress protection:	IP20
Mounting version:	suspended
Cable length [m]:	1.20
Net weight [kg]:	2.350
Warranty [years]:	5
CE certificate:	218/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



