

QUEST 2 LED HB L 47400LM I CL. IP66 757 70D SP10KV (364W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	364
Luminous flux [lm]*:	47400
Colour temperature [K]:	5700
Colour rendering index:	>70
SDCM:	≤ 5
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium

CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

QUEST 2 LED HB L 47400LM I CL. IP66 757 70D SP10KV (364W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	742033	Colour of the body:	RAL 7016
EAN:	5905963742033	Dimensions (H/W/T/S) [mm]:	870/450/45
Rated power of the luminaire [W]:	364	Impact resistance:	IK09
Luminous flux [lm]:	47400	Ingress protection:	IP66
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.180
Luminous efficacy [lm/W]:	130	Mark D:	yes
Energy efficiency class:	D	Net weight [kg]:	10.400
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	5700	Version:	2xL
Colour rendering index:	>70	Light distribution type:	70 UGR<22
SDCM:	≤ 5	Efficiency of the luminaire:	0.93
LED lifespan L70B50 [h]:	156000	Additional accessories:	protective grid
LED lifespan L80B20 [h]:	98000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	47000	Cable length [m]:	0.90
Beam angle [°]:	70	The number of implement units:	4
Surge protection [kV]:	10	Warranty [years]:	5
Diffuser material:	glass	CE certificate:	158/2023
Diffuser type:	transparent	PZH certificate:	B-BK-60212-0480/21
Optics:	lens	Manual:	Download PDF
Material of the body:	aluminium		

QUEST 2 LED HB L 47400LM I CL. IP66 757 70D SP10KV (364W)

DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
699993	QUEST 2 LED M - surface frame
699986	QUEST 2 LED L - surface frame
699948	QUEST 2 LED HB L protective grid RAL7016 single suspension
699955	QUEST 2 LED HB M protective grid RAL7016 single suspension
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016




QUEST 2 LED M - surface frame (699993)



QUEST 2 LED L - surface frame (699986)



QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)

Card creation date: 09 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 158/2023