

# QUEST 2 LED HB NT L 46600LM I CL. IP66 757 125/30D SP10KV (364W)

DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	364
Luminous flux [lm]*:	46600
Colour temperature [K]:	5700
Colour rendering index:	70
SDCM:	≤ 5
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium

## CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

## APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

# QUEST 2 LED HB NT L 46600LM I CL. IP66 757 125/30D SP10KV (364W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE


Index:	742057	Colour of the body:	RAL 7016
EAN:	5905963742057	Dimensions (H/W/T/S) [mm]:	870/510/85
Rated power of the luminaire [W]:	364	Impact resistance:	IK09
Luminous flux [lm]:	46600	Ingress protection:	IP66
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.180
Luminous efficacy [lm/W]:	128	The number of implement units:	4
Energy efficiency class:	D	Mark D:	yes
Electrical protection class:	I	Net weight [kg]:	10.400
Colour temperature [K]:	5700	Version:	2xL
Colour rendering index:	70	Light distribution type:	125/30
SDCM:	≤ 5	Efficiency of the luminaire:	0.93
LED lifespan L70B50 [h]:	156000	Additional accessories:	protective grid
LED lifespan L80B20 [h]:	98000	Cable length [m]:	0.90
LED lifespan L90B10 [h]:	47000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Beam angle [°]:	125/30	Warranty [years]:	5
Surge protection [kV]:	10	CE certificate:	<a href="#">158/2023</a>
Diffuser material:	glass	PZH certificate:	<a href="#">B-BK-60212-0480/21</a>
Diffuser type:	transparent	Environmental Product Declaration (EPD):	<a href="#">816/2025</a>
Optics:	lens	Manual:	<a href="#">Download PDF</a>
Material of the body:	aluminium	Plik LDT:	<a href="#">Download</a>

# QUEST 2 LED HB NT L 46600LM I CL. IP66 757 125/30D SP10KV (364W)


DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699948	QUEST 2 LED HB L protective grid RAL7016 single suspension
699955	QUEST 2 LED HB M protective grid RAL7016 single suspension
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016




QUEST 2 LED M - recessed frame (699993)



QUEST 2 LED L - recessed frame (699986)



QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)