

RQ 100 LED PLUS P DALI 630LM MAT II CL. IP44/20 840 (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44/20
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	630
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matt

CHARACTERISTICS

RQ 100 LED PLUS P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

RQ 100 LED PLUS P DALI 630LM MAT II CL. IP44/20 840 (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	572678	Colour of the body:	white
Rated power of the luminaire [W]:	6	Dimensions (H/W/T/S) [mm]:	102/75
Supply voltage [V]:	220 - 240	Impact resistance:	IK08
Frequency [Hz]:	50 - 60	Ingress protection:	IP44/20
Luminous flux [lm]:	630	Mounting version:	recessed
Luminous efficacy [lm/W]:	102	Working temperature [°C]:	from -25 to +35
Energy efficiency class:	E	Net weight [kg]:	0.300
Electrical protection class:	II	CE certificate:	316/2023
Colour temperature [K]:	4000	Warranty [years]:	5
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	Manual:	Download PDF
Power factor:	0.99	LED lifespan L70B50 [h]:	150000
Beam angle [°]:	105	LED lifespan L80B10 [h]:	100000
Diffuser material:	PC	LED lifespan L90B10 [h]:	50000
Diffuser type:	matt	DIMM DALI:	yes
Diffuser colour:	milky	Plik LDT:	Download
Material of the body:	ABS		

Card creation date: 03 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 316/2023