ASTRA LED BASIC 4400LM 840 IP66 I CL. SP10KV 32W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	664670
Ingress protection:	IP66
Impact resistance:	IK08
Luminous flux [lm]*:	4400
Rated power of the luminaire [W]*:	32
Colour temperature [K]:	4000
SDCM:	3
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	C

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 173 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (FG) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN–EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom).

APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and Mounting: lateral side entry, post-top mounting.Mounting grip integrated with the fitting.

ASTRA LED BASIC 4400LM 840 IP66 I CL. SP10KV 32W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	664670
Light source:	LED module
Rated power of the luminaire [W]:	32
Luminous flux [lm]:	4400
Luminous efficacy [lm/W]:	173
Energy efficiency class:	C
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.93
Diffuser material:	PC
Diffuser type:	matrix led
Diffuser colour:	transparent
Optics material:	PC
Optics:	matrix lens
Dimensions (H/W/T/S) [mm]:	640/113/233
Mounting dimensions [mm]:	ø60
Material of the body:	PP + 35%GF
Ingress protection:	IP66
Impact resistance:	IK08

Colour of the body:	grey
Mounting version:	side, top
Working temperature [°C]:	from -15 to +35
Tilt angle adjustment [°]:	od -5 do +15
Lateral surface (SCx) [m2]:	0.018
Wire type:	H07RN-F
Cable length [m]:	0.50
Protection type:	10
Number on the palette [pcs]:	62
Net weight [kg]:	1.900
Category type:	street lighting
LED lifespan L70B50 [h]:	122000
LED lifespan L80B10 [h]:	77000
LED lifespan L90B10 [h]:	36000
Light distribution type:	uliczny
Manual:	Download PDF
CE certificate:	273/2023
Warranty [years]:	5
ENEC Certificate:	0323/ENEC/23
Category of application:	Street lighting
Plik LDT:	Download

LIGHT CURVES



ASTRA LED BASIC 4400LM 840 IP66 I CL. SP10KV 32W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
598357	Pole adapter 80/60 ALU
UL00214	Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED



Pole adapter 80/60 ALU (598357)



Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 273/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl