ASTRA LED BASIC VD 5350LM 830 IP66 I CL. SP10KV 50W

DETAILED CARD





TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	50
Luminous flux [lm]*:	5350
Colour temperature [K]:	3000
SDCM:	5
Color rendering index (Ra) >:	80
Electrical protection class:	1
Energy efficiency class:	E

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 116 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (FG) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN–EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom).

APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and Mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.



ASTRA LED BASIC VD 5350LM 830 IP66 I CL. SP10KV 50W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	664601
Light source:	LED module
Rated power of the luminaire [W]:	50
Luminous flux [lm]:	5350
Luminous efficacy [lm/W]:	106
Energy efficiency class:	E
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	5
Power factor:	0.93
Diffuser type:	matrix led
Diffuser colour:	transparent
Optics material:	PC
Optics:	matrix lens
Dimensions (H/W/T/S) [mm]:	640/113/233
Mounting dimensions [mm]:	ø60
Ingress protection:	IP66
Impact resistance:	IK08
Colour of the body:	grey

Mounting version:	side, top
Working temperature [°C]:	from -40 to +35
Tilt angle adjustment [°]:	od -5 do +15
Lateral surface (SCx) [m2]:	0.018
Wire type:	H07RN-F
Cable length [m]:	0.50
Protection type:	10
Number on the palette [pcs]:	62
Net weight [kg]:	1.900
Category of application:	Street lighting
LED lifespan L70B50 [h]:	120000
LED lifespan L80B20 [h]:	75000
LED lifespan L90B10 [h]:	36000
Light distribution type:	uliczny
Manual:	Download PDF
CE certificate:	<u>52/2021</u>
Warranty [years]:	5
ULOR:	0%
Plik LDT:	Download

LIGHT CURVES





ASTRA LED BASIC VD 5350LM 830 IP66 I CL. SP10KV 50W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
598357	Pole adapter 80/60 ALU
UL00214	Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED







Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)

Card creation date: 29 October 2025



