

ASTRA LED BASIC VD 7050LM 840 IP66 I CL. SP10KV 65W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK08
Rated power of the luminaire [W]*:	65
Luminous flux [lm]*:	7050
Colour temperature [K]:	4000
SDCM:	5
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	E
Material of the body:	PP + 35%GF

CHARACTERISTICS

Streetlight LED fitting with high luminous flux (max 116 lm/W) and an integrated energy-saving LED module. The self-cleaning body made of polypropylene (PP) with fibreglass (FG) and the grip made of aluminium. Thanks to the directional lens (made of PC), the light distribution meets the requirements of PN-EN 13201 lighting class. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting by 5 degrees in the range of: -5° to +15° (peak to pole); -15° to +5° (side to boom).

APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and Mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.


ASTRA LED BASIC VD 7050LM 840 IP66 I CL. SP10KV 65W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	664755	Colour of the body:	grey
Light source:	LED module	Mounting version:	side, top
Rated power of the luminaire [W]:	65	Working temperature [°C]:	from -40 to +35
Luminous flux [lm]:	7050	Tilt angle adjustment [°]:	od -5 do +15
Luminous efficacy [lm/W]:	101	Lateral surface (SCx) [m2]:	0.018
Energy efficiency class:	E	Wire type:	H07RN-F
Electrical protection class:	I	Cable length [m]:	0.50
Colour temperature [K]:	4000	Protection type:	10
Color rendering index (Ra) >:	80	Number on the palette [pcs]:	62
SDCM:	5	Net weight [kg]:	1.900
Power factor:	0.93	Category of application:	Street lighting
Diffuser type:	matrix led	LED lifespan L70B50 [h]:	120000
Diffuser colour:	transparent	LED lifespan L80B20 [h]:	75000
Optics material:	PC	LED lifespan L90B10 [h]:	36000
Optics:	matrix lens	Light distribution type:	uliczny
Dimensions (H/W/T/S) [mm]:	640/113/233	Manual:	Download PDF
Mounting dimensions [mm]:	ø60	CE certificate:	52/2021
Material of the body:	PP + 35%GF	Warranty [years]:	5
Ingress protection:	IP66	Plik LDT:	Download
Impact resistance:	IK08		

LIGHT CURVES



ASTRA LED BASIC VD 7050LM 840 IP66 I CL. SP10KV 65W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
598357	Pole adapter 80/60 ALU
UL00214	Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED



Pole adapter 80/60 ALU (598357)



Adjustable bracket Astra LED/Astra LED BASIC aluminium grey RAL 9006 diameter 64 mm Corona 2 LED (UL00214)