## COMPACT LED EVO N 4000LM NPRM UGR DALI I CL. IP20 1200X250 840 (32W)

**DETAILED CARD** 





## **TECHNICAL PARAMETERS**

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	32
Luminous flux [lm]*:	4000
Color rendering index (Ra) >:	80
Energy efficiency class:	D
Material of the body:	ABS
Diffuser material:	PC
Diffuser type:	NPRM

#### **CHARACTERISTICS**

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM):  $\leq$ 3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

### APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.



# COMPACT LED EVO N 4000LM NPRM UGR DALI I CL. IP20 1200X250 840 (32W)

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	902680
Light source:	LED module
Nominal power [W]:	32
Luminous flux [lm]:	4000
Luminous efficacy [lm/W]:	121
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Power factor:	0.96
Diffuser material:	PC
Diffuser type:	NPRM
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	1195/250/66
Impact resistance:	IK07
Ingress protection:	IP20

Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Working temperature [°C]:	from -20 to +35
DIMM DALI:	yes
Net weight [kg]:	2.600
Category type:	troffers
LED lifespan L70B50 [h]:	132000
LED lifespan L80B20 [h]:	84000
LED lifespan L90B10 [h]:	42000
Mounting dimensions [mm]:	1137/147
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	<u>361/2023</u>
ENEC Certificate:	PL BBJ/009/2021/M1
PZH certificate:	
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 11 July 2025



