

COMPACT LED EVO N 7000LM NPRM UGR I CL. IP20

1200X250 840 (58W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	58
Luminous flux [lm]*:	7000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PC
Diffuser type:	NPRM

CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

COMPACT LED EVO N 7000LM NPRM UGR I CL. IP20

1200X250 840 (58W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	902673	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Light source:	LED module	Working temperature [°C]:	from -20 to +35
Nominal power [W]:	58	UGR (4H8H):	≤20.9
Luminous flux [lm]:	7000	Net weight [kg]:	2.600
Luminous efficacy [lm/W]:	117	Category type:	louvres
Energy efficiency class:	E	LED lifespan L70B50 [h]:	132000
Electrical protection class:	I	LED lifespan L80B20 [h]:	84000
Colour temperature [K]:	4000	LED lifespan L90B10 [h]:	42000
Colour rendering index:	>80	Mounting dimensions [mm]:	1137/147
Power factor:	0.96	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	NPRM	CE certificate:	361/2023
Material of the body:	ABS	ENEC Certificate:	PL BBJ/009/2021/M1
Colour of the body:	white	PZH certificate:	
Dimensions (H/W/T/S) [mm]:	1195/250/66	Manual:	Download PDF
Impact resistance:	IK07	Plik LDT:	Download
Ingress protection:	IP20		