

# COMPACT LED EVO N 7000LM NPRM UGR I CL. IP20

## 1200X250 840 (58W)

DETAILED CARD



### TECHNICAL PARAMETERS

Ingress protection:	IP20
Impact resistance:	IK07
Nominal power [W]:	58
Luminous flux [lm]*:	7000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PC
Diffuser type:	NPRM

### CHARACTERISTICS

Compact LED luminaire designed for surface mounting or modular ceilings. Equipped with energy-saving LED modules and an evenly highlighted opal diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Standard Deviation Colour Matching (SDCM): ≤3. COMPACT LED EVO N 1200x250 with nPRM nano-prismatic diffuser, can be used wherever low UGR is required.

### APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

# COMPACT LED EVO N 7000LM NPRM UGR I CL. IP20


## 1200X250 840 (58W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Nominal power [W]:	58	Impact resistance:	IK07
Index:	902673	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface mounted; recessed mounted in modular ceiling possible
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	7000	Net weight [kg]:	2.600
Diffuser type:	NPRM	Warranty [years]:	5
Diffuser material:	PC	Category type:	louvres
Luminous efficacy [lm/W]:	117	LED lifespan L70B50 [h]:	132000
Energy efficiency class:	E	LED lifespan L80B20 [h]:	84000
Electrical protection class:	I	LED lifespan L90B10 [h]:	42000
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.96	Mounting dimensions [mm]:	1137/147
Material of the body:	ABS	CE certificate:	<a href="#">361/2023</a>
Colour of the body:	white	PZH certificate:	
Dimensions (H/W/T/S) [mm]:	1195/250/66	Warranty [years]:	5
		Manual:	<a href="#">Download PDF</a>
		ENEC Certificate:	<a href="#">PL BBJ/009/2021/M1</a>
		UGR (4H8H):	≤20.9
		Plik LDT:	<a href="#">Download</a>

### LIGHT CURVES



Card creation date: 08 January 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 361/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)