


ELEGANTE SYSTEM LED CONNECTOR L 315X315MM

1200LM OPAL DALI IP40 840 (15W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	388057
Ingress protection:	IP40/20
Impact resistance:	IK04
Nominal power [W]:	15
Luminous flux [lm]*:	1200
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	G
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution. Available system switches allow for the design of concealed light lines in various configurations (T, X, L). The advantage of the system's roofs is the lampshade without connections to max. length 25m.

There is also a version of individual fittings.

Available 2 power options - to connect as part of:

- 16W i 8W,
- 30W i 15W.

Assembly should be carried out by qualified person.

Please feel free to contact our lighting designers.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.

ELEGANTE SYSTEM LED CONNECTOR L 315X315MM

1200LM OPAL DALI IP40 840 (15W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	Colour of the body:	silver
Light source:	LED module	Mounting dimensions [mm]:	315/55/315/55
Colour temperature [K]:	4000	Impact resistance:	IK04
Luminous flux [lm]:	1200	Mounting version:	recessed
Rated power of the luminaire [W]:	18.46	Working temperature [°C]:	from -20 to +35
Diffuser type:	OPAL	Accessories included:	diffuser
Supply voltage [V]:	220-240	Through wiring:	5x2.5
DIMM DALI:	yes	Net weight [kg]:	1.600
Frequency [Hz]:	50 - 60	Gross weight [kg]:	1.900
Version:	L connector	Index:	388057
Source luminous flux [lm]*:	2304	EAN:	5905963388057
Dimensions (H/W/T/S) [mm]:	315/315/65	Category type:	systems
Ingress protection:	IP40/20	Product line:	SYSTEM 30W/15W
Luminous efficacy [lm/W]:	65	Light distribution type:	open space
Energy efficiency class:	G	Kolejność:	D
Electrical protection class:	I	ETIM class:	EC000282
Colour rendering index:	>80	CE certificate:	244/2023
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Power factor:	0.91	Warranty [years]:	5
Diffuser material:	PC	Manual:	Download PDF
Diffuser colour:	white	Plik LDT:	Download
Material of the body:	aluminium		

ELEGANTE SYSTEM LED CONNECTOR L 315X315MM

1200LM OPAL DALI IP40 840 (15W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 244/2023