

ELEGANTE SYSTEM LED S 1123MM 1400LM OPAL DALI IP44 830 (16W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	388538
Ingress protection:	IP44/20
Impact resistance:	IK04
Nominal power [W]:	16
Luminous flux [lm]*:	1400
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	aluminium
Colour of the body:	silver

CHARACTERISTICS

ELEGANTE LED SYSTEM is a modern office fixture designed for flush mounting. It provides a combination of high light parameters and a modern decorative effect. The optical design has been designed using an iridescent diaphragm with high permeability and uniform light distribution. Available system switches allow for the design of concealed light lines in various configurations (T, X, L). The advantage of the system's roofs is the lampshade without connections to max. length 25m.

There is also a version of individual fittings.

Available 2 power options - to connect as part of:

- 16W i 8W,
- 30W i 15W.

Assembly should be carried out by qualified person.

Please feel free to contact our lighting designers.

APPLICATION

The luminaire is dedicated for internal use. For use in office and commercial facilities, in particular in representative rooms.

ELEGANTE SYSTEM LED S 1123MM 1400LM OPAL DALI IP44 830 (16W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	16	Material of the body:	aluminium
Light source:	LED module	Colour of the body:	silver
Colour temperature [K]:	3000	Mounting dimensions [mm]:	1123/55
Luminous flux [lm]:	1400	Impact resistance:	IK04
Rated power of the luminaire [W]:	16.19	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
DIMM DALI:	yes	Net weight [kg]:	2.200
Frequency [Hz]:	50 - 60	Gross weight [kg]:	2.600
Version:	start module	Index:	388538
Source luminous flux [lm]*:	2446	EAN:	5905963388538
Dimensions (H/W/T/S) [mm]:	1123/90/65	Category type:	systems
Ingress protection:	IP44/20	Product line:	SYSTEM 16W/8W
Luminous efficacy [lm/W]:	86	LED lifespan L80B20 [h]:	73000
Energy efficiency class:	F	LED lifespan L90B10 [h]:	36000
Electrical protection class:	I	Light distribution type:	open space
Colour rendering index:	>80	Kolejność:	A
SDCM:	≤ 3	ETIM class:	EC000282
Power factor:	0.92	CE certificate:	244/2023
LED lifespan L70B50 [h]:	115000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	Warranty [years]:	5
Diffuser colour:	white	Manual:	Download PDF
		Plik LDT:	

ELEGANTE SYSTEM LED S 1123MM 1400LM OPAL DALI IP44 830 (16W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
81000945	ELEGANTE LED SYSTEM - OPAL diffuser - 1 rm (max 25 rm)
388736	ELEGANTE SYSTEM LED end set
388743	ELEGANTE SYSTEM LED gniazdo 3 polowe
388750	ELEGANTE SYSTEM LED gniazdo 5 polowe
388767	ELEGANTE SYSTEM LED wtyk 3 polowy
388774	ELEGANTE SYSTEM LED wtyk 5 polowy
388729	ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m



ELEGANTE SYSTEM LED gniazdo 3 polowe (388743)



ELEGANTE SYSTEM LED gniazdo 5 polowe (388750)



ELEGANTE SYSTEM LED wtyk 3 polowy (388767)



ELEGANTE SYSTEM LED wtyk 5 polowy (388774)



ELEGANTE SYSTEM LED klosz PC opal co-extrusion+soft fixing part 25m (388729)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 244/2023