
TERRA 2 LED LONG N X2 1195X140MM 2550LM 840 WHITE-BLACK MAT (31W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	227028
Ingress protection:	IP20
Nominal power [W]:	31
Luminous flux [lm]*:	2550
Color rendering index (Ra) >:	80
SDCM:	3

Material of the body: powder coated steel

Mounting version: surface

Dimensions (H/W/T/S) [mm]: 1195/140/36

Warranty [years]: 5

CHARACTERISTICS

LED luminaire with high total luminous Flux. Made of powder coated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface, recessed in modular and suspended. The surface-mounted version uses solutions that enhance the speed and safety of installation. A multitude of versions & dimentions allow to replace worn-out recessed fluorescent luminaires.

APPLICATION

General purpose surface mounted luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.



TERRA 2 LED LONG N X2 1195X140MM 2550LM 840 WHITE-BLACK MAT (31W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	227028
Light source:	LED module
Nominal power [W]:	31
Rated power of the luminaire [W]:	34
Supply voltage [V]:	220 - 240
Luminous flux [Im]:	2550
Luminous efficacy [lm/W]:	75
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
Optics:	black HE
Material of the body:	powder coated steel
Colour of the body:	white mat
Dimensions (H/W/T/S) [mm]:	1195/140/36

Ingress protection:	IP20
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Category type:	troffers
Category of application:	educational institutions, commercial facilities
Version:	2x1
AC voltage range [V]:	220 - 240
UGR (4H8H):	< 16.7
LED lifespan L70B50 [h]:	132000
LED lifespan L80B20 [h]:	84000
LED lifespan L90B10 [h]:	42000
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	354/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 28 October 2025



