

QUEST 2 LED L ASW 26300LM I CL. IP66 740 SP10KV (210W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	699818
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	210
Luminous flux [lm]*:	26300
Colour temperature [K]:	4000
Colour rendering index:	>70
SDCM:	≤ 5
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

High-quality floodlight with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass. It is equipped with directional lens matrices with 3 different light distributions: symmetrical (120°), asymmetric narrow ASN and asymmetric wide ASW. Non-corrosive mounting bracket allowing for adjustment angles between -140° to +185°. The luminaire is available in 2 sizes: M and L. Standard equipped with 0.1m long H07RN-F cable and IP66 quick connector. Wide range of accessories available: protective net, grip for the lighting pole, wall bracket.

APPLICATION

The fitting is dedicated for lighting elevations and billboards.

QUEST 2 LED L ASW 26300LM I CL. IP66 740 SP10KV (210W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	210	Colour of the body:	RAL 7016
Index:	699818	Dimensions (H/W/T/S) [mm]:	415/424/37
Colour temperature [K]:	4000	Impact resistance:	IK09
Light source:	LED	Ingress protection:	IP66
Luminous flux [lm]:	26300	Mounting version:	surface
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.180
Beam angle [°]:	ASW	Net weight [kg]:	5.200
Version:	L	Warranty [years]:	5
Luminous efficacy [lm/W]:	125	LED lifespan L70B50 [h]:	118000
Energy efficiency class:	D	LED lifespan L80B20 [h]:	74000
Electrical protection class:	I	LED lifespan L90B10 [h]:	37000
Colour rendering index:	>70	Cable length [m]:	0.90
SDCM:	≤ 5	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Light distribution type:	asymmetric ASW	Mark D:	1
Surge protection [kV]:	10	Additional accessories:	protective grid, pole mount, wall mount
Diffuser material:	glass	The number of implement units:	2
Diffuser type:	transparent	Warranty [years]:	5
Optics material:	PC	CE certificate:	86/2021
Optics:	lens	PZH certificate:	B-BK-60212-0480/21
Material of the body:	aluminium	Manual:	Download PDF
		Plik LDT:	Pobierz

QUEST 2 LED L ASW 26300LM I CL. IP66 740 SP10KV (210W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
559938	QUEST PLUS LED M/L wall holder RAL9006
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016
965913	QUEST 2 LED M/L MAX wall mount RAL7016
567728	QUEST 2 LED M/L Pole holder




QUEST PLUS LED M/L wall holder RAL9006 (559938)



QUEST 2 LED M - recessed frame (699993)



QUEST 2 LED L - recessed frame (699986)




QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)



QUEST 2 LED M/L MAX wall mount RAL7016 (965913)



QUEST 2 LED M/L Pole holder (567728)

Card creation date: 16 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 86/2021