

SOLANTO MULTI Z 600MM+900MM 2080-3520LM 840 IP20 I CL. OPAL WHITE 26-44W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	26 – 44
Luminous flux of the luminaire [lm] - range:	2080-3520
Colour temperature [K]:	4000
Energy efficiency class:	D
Diffuser material:	PS
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	Ø 900/32,Ø 602/32

CHARACTERISTICS

Suspended LED luminaire composed of two rings (602 and 900mm), allowing for attractive arrangement of representative interiors. The luminaire is made of powder-coated steel in white, black, or any other color which matches the character of the interior. The diffusers made with thermoforming method emphasize the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED version allows to choose from 4 lumens and power settings increasing its versatility and functionality and at the same time reducing the number of indexes to the minimum.

APPLICATION

SOLANTO DUO is a very impressive pendant luminaire dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can also be used in flats or apartments and perfectly fits into stylish surroundings.

SOLANTO MULTI Z 600MM+900MM 2080-3520LM 840 IP20 I CL. OPAL WHITE 26-44W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463563	Diffuser type:	OPAL
EAN:	5905963463563	Diffuser colour:	milky
Light source:	LED module	Material of the body:	Steel
Rated power [W] - range:	26 – 44	Colour of the body:	white
Luminous flux of the luminaire [lm] - range:	2080-3520	Dimensions (H/W/T/S) [mm]:	Ø 900/32,Ø 602/32
Colour temperature [K]:	4000	Ingress protection:	IP20
Supply voltage [V]:	220 - 240	Mounting version:	suspended
Frequency [Hz]:	50 - 60	Cable length [m]:	1.20
Luminous efficacy [lm/W]:	80	Number on the palette [pcs]:	1
Energy efficiency class:	D	Net weight [kg]:	6.500
Electrical protection class:	I	Warranty [years]:	5
Colour rendering index:	>80	CE certificate:	219/2023
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	116600	Manual:	Download PDF
LED lifespan L80B20 [h]:	73 600	Category type:	architectural
LED lifespan L90B10 [h]:	35700	Category of application:	HoReCa, art and culture
Diffuser material:	PS		

Card creation date: 20 July 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 219/2023