

SOLANTO Z 600MM+900MM 4300LM 840 IP20 I CL. OPAL WHITE 54W

DETAILED CARD



TECHNICAL PARAMETERS

Rated power [W] - range:	54
Luminous flux of the luminaire [lm] - range:	4300
Colour temperature [K]:	4000
Energy efficiency class:	D
Diffuser material:	PS
Diffuser type:	OPAL
Diffuser colour:	milky
Material of the body:	Steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	Ø 900/32,Ø 602/32

CHARACTERISTICS

Suspended LED luminaire composed of two rings (602 and 900mm), allowing for attractive arrangement of representative interiors. The luminaire is made of powder-coated steel in white, black, or any other color which matches the character of the interior. The diffusers made with thermoforming method emphasize the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED version allows to choose from 4 lumens and power settings increasing its versatility and functionality and at the same time reducing the number of indexes to the minimum.

APPLICATION

SOLANTO DUO is a very impressive pendant luminaire dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can also be used in flats or apartments and perfectly fits into stylish surroundings.

SOLANTO Z 600MM+900MM 4300LM 840 IP20 I CL. OPAL WHITE 54W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463587	Diffuser colour:	milky
EAN:	5905963463587	Material of the body:	Steel
Light source:	LED module	Colour of the body:	white
Rated power [W] - range:	54	Dimensions (H/W/T/S) [mm]:	Ø 900/32,Ø 602/32
Luminous flux of the luminaire [lm] - range:	4300	Ingress protection:	IP20
Colour temperature [K]:	4000	Mounting version:	suspended
Supply voltage [V]:	220 - 240	Cable length [m]:	1.20
Frequency [Hz]:	50 - 60	Number on the palette [pcs]:	1
Energy efficiency class:	D	Net weight [kg]:	6.500
Electrical protection class:	I	Warranty [years]:	5
Color rendering index (Ra) >:	80	CE certificate:	219/2023
SDCM:	3	Warranty [years]:	5
LED lifespan L70B50 [h]:	116600	Manual:	Download PDF
LED lifespan L80B10 [h]:	73 600	Category type:	decorative fixtures
LED lifespan L90B10 [h]:	35700	Category of application:	HoReCa
Diffuser material:	PS	Plik LDT:	Download
Diffuser type:	OPAL		

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 219/2023