

UV-C STERILON 36W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	36
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	PP
Dimensions (H/W/T/S) [mm]:	215/320/95
Ingress protection:	IP20
Mounting version:	mounting on a tripod or wall bracket
Direct surface disinfection function:	yes

CHARACTERISTICS

UV-C STERILON lamps emitting ultraviolet light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is enough to direct the UV lamp directly onto the surface for a specified time to effectively kill microorganisms. They are so powerful that they may produce harmful effects on human skin or eyes. Therefore, basic safety precautions should be observed when using UVC lamps for disinfection, i.e. you should not stay within the range of the light beam.

APPLICATION

Lamps with power 36W will disinfect a space of about 15m². There are recommended for use in healthcare facilities, grocery stores, public and private means of transport, at petrol stations, in courier companies, public administration, and educational establishments. Depending on the distance from the light source, temperature and humidity, we take 15 minutes as an approximate disinfection time.

UV-C STERILON 36W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	243943	Service life of the UV-C radiation source [h]:	9000
Category type:	bactericidal and virucidal lamps	Type of direct surface disinfection:	one-way
Product line:	UV-C STERILON	Internal element emitting UV-C radiation [W]:	2x18
Light source:	UV-C	CE certificate:	439/2023
Nominal power [W]:	36	PZH certificate:	B-BK-60212-0217/20
Supply voltage [V]:	220 - 240	Warranty [years]:	2
Electrical protection class:	I	Manual:	Download PDF
Exchangeable source:	yes	EAN:	5905963243943
Material of the body:	PP	Frequency [Hz]:	50 - 60
Colour of the body:	white	Luminous efficacy [lm/W]:	1
Dimensions (H/W/T/S) [mm]:	215/320/95	Energy efficiency class:	G
Ingress protection:	IP20	Light colour:	violet
Mounting version:	mounting on a tripod or wall bracket	LED lifespan L70B50 [h]:	9000
Plug type:	UNI-SCHUKO	Working temperature [°C]:	from -20 to +45
Cable length [m]:	5	Operating mode:	no
Switch:	yes	Control:	no
Net weight [kg]:	1.380	Master/slave:	no
Total power consumption [W]:	36	Through wiring:	no
UV-C wavelength [nm]:	253.70	Protection type:	mo
Direct surface disinfection function:	yes	Number in carton box [pcs]:	1
Illumination area at a distance of 1 m:	15	Number on the palette [pcs]:	72
Type of light:	ultraviolet UV-C		

UV-C STERILON 36W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000720	Standard tripod
243615	Magnetic holder UV-C Sterilon 36W
243622	Ceiling holder UV-C Sterilon 180x180x12mm
243639	UV-C protective glasses
160UV003	TC-L UV-C 18W 2G11 TUV fluorescent lamp



Standard tripod (000720)



UV-C protective glasses (243639)

Card creation date: 08 March 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 439/2023