

UV-C STERILON FLOW 72W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	72
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/160
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	yes
Max volume of the disinfected room [m³]:	75
Direct surface disinfection function:	yes

CHARACTERISTICS

UV-C STERILON FLOW 72W luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 72W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240416	Type of light:	ultraviolet UV-C
Category type:	bactericidal and virucidal lamps	Protection against opening:	yes
Product line:	UV-C STERILON	Noise intensity [dB]:	42
Light source:	UV-C	Internal element emitting UV-C radiation [W]:	2x36
Nominal power [W]:	72	EAN:	5905963240416
Service life of the UV-C radiation source [h]:	9000	Frequency [Hz]:	50 - 60
Supply voltage [V]:	220 - 240	Luminous efficacy [lm/W]:	2.40
Electrical protection class:	I	Light colour:	violet
Exchangeable source:	yes	LED lifespan L70B50 [h]:	9000
Material of the body:	carbon steel	Working temperature [°C]:	from -20 to +45
Colour of the body:	white/silver	Operating mode:	no
Dimensions (H/W/T/S) [mm]:	724/160/160	Control:	yes
Ingress protection:	IP20	Master/slave:	no
Mounting version:	detached	Through wiring:	no
Plug type:	UNI-SCHUKO	Protection type:	yes
Version:	dual-purpose	Number in carton box [pcs]:	1
Cable length [m]:	3	Number on the palette [pcs]:	28
Switch:	yes	Direct surface disinfection function:	yes
Total power consumption [W]:	82	Illumination area at a distance of 1 m:	7
UV-C wavelength [nm]:	253.70	Warranty [years]:	2
Dust filter:	yes	CE certificate:	324/2023
Flow air disinfection function:	yes	PZH certificate:	B-BK-60212-0317/20
Max volume of the disinfected room [m3]:	75	Manual:	Download PDF
HEPA filter holder:	yes		
Air flow [m3 / h]:	160		

UV-C STERILON FLOW 72W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240485	Wall bracket STERILON FLOW 72W
243646	Set of guide wheels Sterilon Flow 72W matt white
243677	HEPA H10 filter - set of 5 only for the Flow model
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
243639	UV-C protective glasses



Set of guide wheels Sterilon Flow 72W matt white (243646)



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 324/2023