


UV-C STERILON FLOW 144W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	144
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/220
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	yes
Max volume of the disinfected room [m³]:	120
Direct surface disinfection function:	yes

CHARACTERISTICS

UV-C STERILON FLOW 144W luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 144W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	246463	Type of light:	ultraviolet UV-C
Light source:	UV-C	Noise intensity [dB]:	44
Nominal power [W]:	144	Internal element emitting UV-C radiation [W]:	4x36
Service life of the UV-C radiation source [h]:	9000	EAN:	5905963246463
Supply voltage [V]:	220 - 240	Frequency [Hz]:	50 - 60
Electrical protection class:	I	Luminous efficacy [lm/W]:	4.80
Exchangeable source:	yes	Light colour:	violet
Material of the body:	carbon steel	LED lifespan L70B50 [h]:	9000
Colour of the body:	white/silver	Working temperature [°C]:	from -20 to +45
Dimensions (H/W/T/S) [mm]:	724/160/220	Operating mode:	no
Ingress protection:	IP20	Control:	yes
Mounting version:	detached	Master/slave:	no
Plug type:	UNI-SCHUKO	Through wiring:	no
Version:	dual-purpose	Protection type:	mo
Cable length [m]:	3	Number in carton box [pcs]:	1
Switch:	yes	Number on the palette [pcs]:	20
Net weight [kg]:	10.270	Direct surface disinfection function:	yes
Gross weight [kg]:	11	Illumination area at a distance of 1 m:	14
Total power consumption [W]:	155	Warranty [years]:	2
UV-C wavelength [nm]:	253.70	CE certificate:	324/2023
Dust filter:	yes	PZH certificate:	B-BK-60212-0317/20
Flow air disinfection function:	yes	Manual:	Download PDF
Max volume of the disinfected room [m3]:	120		
HEPA filter holder:	yes		
Air flow [m3 / h]:	200		

UV-C STERILON FLOW 144W


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240492	Wall bracket STERILON FLOW 144W
243660	Set of guide wheels Sterilon Flow 144W white matt
243677	HEPA H10 filter - set of 5 only for the Flow model
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
243639	UV-C protective glasses



Set of guide wheels Sterilon Flow 144W white matt (243660)



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 324/2023