


UV-C STERILON FLOW 144W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	144
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/220
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	1
Max volume of the disinfected room [m ³]:	120
Direct surface disinfection function:	1

CHARACTERISTICS

UV-C STERILON FLOW 144W luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 144W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240553
Light source:	UV-C
Nominal power [W]:	144
Service life of the UV-C radiation source [h]:	9000
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Exchangeable source:	1
Material of the body:	carbon steel
Colour of the body:	white/silver
Dimensions (H/W/T/S) [mm]:	724/160/220
Ingress protection:	IP20
Mounting version:	detached
Plug type:	UNI-SCHUKO
Version:	dual-purpose
Cable length [m]:	3
Switch:	1
Net weight [kg]:	10.310
Gross weight [kg]:	11
Total power consumption [W]:	155
UV-C wavelength [nm]:	253.70
Dust filter:	1
Flow air disinfection function:	1
Max volume of the disinfected room [m3]:	120
Working time counter:	1
HEPA filter holder:	1

Air flow [m3 / h]:	200
Type of light:	ultraviolet UV-C
Protection against opening:	1
Noise intensity [dB]:	44
Internal element emitting UV-C radiation [W]:	4x36
EAN:	5905963240553
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	4.80
Light colour:	violet
LED lifespan L70B50 [h]:	9000
Working temperature [°C]:	from -20 to +45
Operating mode:	no
Control:	yes
Master/slave:	no
Through wiring:	no
Protection type:	yes
Number in carton box [pcs]:	1
Number on the palette [pcs]:	20
Direct surface disinfection function:	1
Illumination area at a distance of 1 m:	14
Warranty [years]:	2
CE certificate:	324/2023
PZH certificate:	B-BK-60212-0317/20
Manual:	Download PDF

UV-C STERILON FLOW 144W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240492	Wall bracket STERILON FLOW 144W
243660	Set of guide wheels Sterilon Flow 144W white matt
243677	HEPA H10 filter - set of 5 only for the Flow model
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
243639	UV-C protective glasses



Set of guide wheels Sterilon Flow 144W white matt (243660)



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 324/2023