

UV-C STERILON FLOW 144W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	144
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/220
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	yes
Max volume of the disinfected room [m³]:	120
Direct surface disinfection function:	yes

CHARACTERISTICS

UV-C STERILON FLOW 144W luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 144W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240539	Air flow [m³ / h]:	200
Light source:	UV-C	Type of light:	ultraviolet UV-C
Nominal power [W]:	144	Service life of the UV-C radiation source [h]:	9000
Supply voltage [V]:	220 - 240	Noise intensity [dB]:	44
Electrical protection class:	I	Internal element emitting UV-C radiation [W]:	4x36
Exchangeable source:	yes	EAN:	5905963240539
Material of the body:	carbon steel	Frequency [Hz]:	50 - 60
Colour of the body:	white/silver	Luminous efficacy [lm/W]:	4.80
Dimensions (H/W/T/S) [mm]:	724/160/220	Light colour:	violet
Ingress protection:	IP20	LED lifespan L70B50 [h]:	9000
Mounting version:	detached	Working temperature [°C]:	from -20 to +45
Version:	dual-purpose	Operating mode:	no
Plug type:	UNI-SCHUKO	Control:	yes
Cable length [m]:	3	Master/slave:	no
Switch:	yes	Through wiring:	no
Net weight [kg]:	10.500	Protection type:	no
Gross weight [kg]:	11.190	Number in carton box [pcs]:	1
Total power consumption [W]:	155	Number on the palette [pcs]:	20
UV-C wavelength [nm]:	253.70	Direct surface disinfection function:	yes
Dust filter:	yes	Illumination area at a distance of 1 m:	14
Flow air disinfection function:	yes	Warranty [years]:	2
Max volume of the disinfected room [m³]:	120	CE certificate:	324/2023
Working time counter:	yes	PZH certificate:	B-BK-60212-0317/20
HEPA filter holder:	yes	Manual:	Download PDF

UV-C STERILON FLOW 144W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240492	Wall bracket STERILON FLOW 144W
243660	Set of guide wheels Sterilon Flow 144W white matt
243677	HEPA H10 filter - set of 5 only for the Flow model
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
243639	UV-C protective glasses



Set of guide wheels Sterilon Flow 144W white matt (243660)



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 324/2023