

UV-C STERILON AIR 72W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	72
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Exchangeable source:	yes
Dimensions (H/W/T/S) [mm]:	600/148/148
Ingress protection:	IP20
Mounting version:	investment version to be connected to the electrical installation
Flow air disinfection function:	yes
Max volume of the disinfected room [m3]:	90

CHARACTERISTICS

V-C STERILON AIR luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. The luminaires are intended for wall mounting but are also available in a free-standing version. Selected versions are equipped with a 3-meter power cord and a switch. The luminaire is equipped with ECO mode, which makes its operation quieter.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON AIR 72W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240607	ECO mode:	yes
Light source:	UV-C	Protection against opening:	yes
Nominal power [W]:	72	Service life of the UV-C radiation source [h]:	9000
Supply voltage [V]:	220 - 240	Noise intensity [dB]:	41
Electrical protection class:	I	Noise level in ECO mode [dB]:	37
Exchangeable source:	yes	Internal element emitting UV-C radiation [W]:	2x36
Material of the body:	carbon steel	EAN:	5905963240607
Colour of the body:	white / endcap gray	Frequency [Hz]:	50 - 60
Dimensions (H/W/T/S) [mm]:	600/148/148	Luminous efficacy [lm/W]:	2.40
Ingress protection:	IP20	Light colour:	violet
Mounting version:	investment version to be connected to the electrical installation	LED lifespan L70B50 [h]:	9000
Plug type:	UNI-SCHUKO	Working temperature [°C]:	from -20 to +45
Cable length [m]:	3	Operating mode:	no
Net weight [kg]:	3.400	Control:	no
Gross weight [kg]:	4.260	Master/slave:	no
Total power consumption [W]:	73	Through wiring:	no
UV-C wavelength [nm]:	253.70	Protection type:	mo
Dust filter:	yes	Number in carton box [pcs]:	1
Flow air disinfection function:	yes	Number on the palette [pcs]:	48
Max volume of the disinfected room [m3]:	90	Warranty [years]:	2
Working time counter:	yes	CE certificate:	335/2023
Air flow [m3 / h]:	160	PZH certificate:	B-BK-60212-0110/21
Air flow in ECO mode [m3 / h]:	110	Manual:	Download PDF
Type of light:	ultraviolet UV-C		

UV-C STERILON AIR 72W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 26 August 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 335/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl