

# UV-C STERILON AIR 72W

DETAILED CARD



## TECHNICAL PARAMETERS

Nominal power [W]:	72
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Exchangeable source:	1
Dimensions (H/W/T/S) [mm]:	600/148/148
Ingress protection:	IP20
Mounting version:	investment version to be connected to the electrical installation
Flow air disinfection function:	1
Max volume of the disinfected room [m3]:	90

## CHARACTERISTICS

V-C STERILON AIR luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. The luminaires are intended for wall mounting but are also available in a free-standing version. Selected versions are equipped with a 3-meter power cord and a switch. The luminaire is equipped with ECO mode, which makes its operation quieter.

## APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

# UV-C STERILON AIR 72W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	240607	<b>Type of light:</b>	ultraviolet UV-C
<b>Light source:</b>	UV-C	<b>ECO mode:</b>	1
<b>Nominal power [W]:</b>	72	<b>Protection against opening:</b>	1
<b>Service life of the UV-C radiation source [h]:</b>	9000	<b>Noise intensity [dB]:</b>	41
<b>Supply voltage [V]:</b>	220 - 240	<b>Noise level in ECO mode [dB]:</b>	37
<b>Electrical protection class:</b>	I	<b>Internal element emitting UV-C radiation [W]:</b>	2x36
<b>Exchangeable source:</b>	1	<b>EAN:</b>	5905963240607
<b>Material of the body:</b>	carbon steel	<b>Frequency [Hz]:</b>	50 - 60
<b>Colour of the body:</b>	white / endcap gray	<b>Luminous efficacy [lm/W]:</b>	2.40
<b>Dimensions (H/W/T/S) [mm]:</b>	600/148/148	<b>Light colour:</b>	violet
<b>Plug type:</b>	UNI-SCHUKO	<b>LED lifespan L70B50 [h]:</b>	9000
<b>Ingress protection:</b>	IP20	<b>Working temperature [°C]:</b>	from -20 to +45
<b>Cable length [m]:</b>	3	<b>Operating mode:</b>	no
<b>Mounting version:</b>	investment version to be connected to the electrical installation	<b>Control:</b>	no
<b>Net weight [kg]:</b>	3.400	<b>Master/slave:</b>	no
<b>Gross weight [kg]:</b>	4.260	<b>Through wiring:</b>	no
<b>Total power consumption [W]:</b>	73	<b>Protection type:</b>	mo
<b>UV-C wavelength [nm]:</b>	253.70	<b>Number in carton box [pcs]:</b>	1
<b>Dust filter:</b>	1	<b>Number on the palette [pcs]:</b>	48
<b>Flow air disinfection function:</b>	1	<b>Warranty [years]:</b>	2
<b>Max volume of the disinfected room [m3]:</b>	90	<b>CE certificate:</b>	<a href="#">335/2023</a>
<b>Working time counter:</b>	1	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0110/21</a>
<b>Air flow [m3 / h]:</b>	160	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Air flow in ECO mode [m3 / h]:</b>	110		

# UV-C STERILON AIR 72W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 26 August 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 335/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl