

UV-C STERILON AIR 144W

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	144
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	600/148/148
Ingress protection:	IP20
Mounting version:	wall version with a cord for the socket
Flow air disinfection function:	1
Max volume of the disinfected room [m3]:	150

CHARACTERISTICS

UV-C STERILON AIR luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. The luminaires are intended for wall mounting but are also available in a free-standing version. Selected versions are equipped with a 3-meter power cord and a switch. The luminaire is equipped with ECO mode, which makes its operation quieter.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON AIR 144W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240591	Air flow [m³ / h]:	220
Category type:	bactericidal and virucidal lamps	Air flow in ECO mode [m³ / h]:	110
Product line:	UV-C STERILON	Type of light:	ultraviolet UV-C
Light source:	UV-C	ECO mode:	1
Nominal power [W]:	144	Protection against opening:	1
Service life of the UV-C radiation source [h]:	9000	Noise intensity [dB]:	49
Supply voltage [V]:	220 - 240	Noise level in ECO mode [dB]:	37
Electrical protection class:	I	Internal element emitting UV-C radiation [W]:	4x36
Exchangeable source:	1	EAN:	5905963240591
Material of the body:	carbon steel	Frequency [Hz]:	50 - 60
Colour of the body:	white / endcap gray	Luminous efficacy [lm/W]:	4.80
Dimensions (H/W/T/S) [mm]:	600/148/148	Light colour:	violet
Plug type:	UNI-SCHUKO	LED lifespan L70B50 [h]:	9000
Ingress protection:	IP20	Working temperature [°C]:	from -20 to +45
Cable length [m]:	3	Operating mode:	no
Mounting version:	wall version with a cord for the socket	Control:	no
Switch:	1	Master/slave:	no
Net weight [kg]:	4.010	Through wiring:	no
Gross weight [kg]:	4.740	Protection type:	mo
Total power consumption [W]:	142	Number in carton box [pcs]:	1
UV-C wavelength [nm]:	253.70	Number on the palette [pcs]:	20
Dust filter:	1	Warranty [years]:	2
Flow air disinfection function:	1	CE certificate:	335/2023
Max volume of the disinfected room [m³]:	150	PZH certificate:	B-BK-60212-0110/21
Working time counter:	1	Manual:	Download PDF

UV-C STERILON AIR 144W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 335/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl