UV-C STERILON AIR 144W

DETAILED CARD





TECHNICAL PARAMETERS

Nominal power [W]: 144

Supply voltage [V]: 220 - 240

Electrical protection class:

Material of the body: powder coated carbon

steel

150

Dimensions (H/W/T/S) [mm]: 679/148/148

Ingress protection: IP20

Mounting version: standing version with a cable for the socket

Flow air disinfection function: yes

Max volume of the disinfected room

[m3]:

CHARACTERISTICS

UV-C STERILON AIR luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, mold from the surface or destroying the DNA or RNA of any exposed microorganisms. The luminaires are intended for wall mounting but are also available in a free-standing version. Selected versions are equipped with a 3-meter power cord and a switch. The luminaire is equipped with ECO mode, which makes its operation quieter.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.



UV-C STERILON AIR 144W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240652
Category type:	bactericidal and virucidal lamps
Product line:	UV-C STERILON
Light source:	UV-C
Nominal power [W]:	144
Supply voltage [V]:	220 - 240
Electrical protection class:	1
Exchangeable source:	yes
Material of the body:	powder coated carbon steel
Colour of the body:	white / endcap gray
Dimensions (H/W/T/S) [mm]:	679/148/148
Ingress protection:	IP20
Mounting version:	standing version with a cable for the socket
Plug type:	UNI-SCHUKO
Cable length [m]:	3
Switch:	yes
Net weight [kg]:	5.280
Gross weight [kg]:	5.820
Total power consumption [W]:	142
UV-C wavelength [nm]:	253.70
Dust filter:	yes
Flow air disinfection function:	yes
Max volume of the disinfected room [m3]:	150
Working time counter:	yes
Air flow [m3 / h]:	220

Type of light: ECO mode: Protection against opening: Service life of the UV-C radiation source [h]: Noise intensity [dB]: Noise level in ECO mode [dB]: ultraviolet UV-C yes yes 9000 49 37	
Protection against opening: Service life of the UV-C radiation source [h]: Noise intensity [dB]: 49	
Service life of the UV-C radiation source [h]: 9000 Noise intensity [dB]: 49	
Noise intensity [dB]: 49	
Noise level in ECO mode [dB]: 37	
Internal element emitting UV-C radiation [W]: 4x36	
EAN: 5905963240652	
Frequency [Hz]: 50 - 60	
Luminous efficacy [Im/W]: 4.80	
Light colour: violet	
LED lifespan L70B50 [h]: 9000	
Working temperature [°C]: from -20 to +45	
Control: no	
Master/slave: no	
Through wiring:	
Protection type: mo	
Number in carton box [pcs]:	
Number on the palette [pcs]: 48	
Warranty [years]: 2	
CE certificate: 334/2023	
PZH certificate: B-BK-60212-0110/21	
Manual: Download PDF	



UV-C STERILON AIR 144W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

