

# UV-C STERILON FLOW 72W MONO

DETAILED CARD



## TECHNICAL PARAMETERS

Nominal power [W]:	72
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/160
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	1
Max volume of the disinfected room [m3]:	60

## CHARACTERISTICS

UV-C STERILON FLOW 72W MONO luminaire emitting ultraviolet (UV-C) light is one of the most effective devices capable of removing viruses, bacteria, fungi from the environment or destroying the DNA or RNA of any exposed microorganisms.

## APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

# UV-C STERILON FLOW 72W MONO

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	240515	<b>Air flow [m<sup>3</sup> / h]:</b>	110
<b>Category type:</b>	bactericidal and virucidal lamps	<b>Type of light:</b>	ultraviolet UV-C
<b>Product line:</b>	UV-C STERILON	<b>Protection against opening:</b>	1
<b>Light source:</b>	UV-C	<b>Noise intensity [dB]:</b>	41
<b>Nominal power [W]:</b>	72	<b>Internal element emitting UV-C radiation [W]:</b>	2x36
<b>Service life of the UV-C radiation source [h]:</b>	9000	<b>EAN:</b>	5905963240515
<b>Supply voltage [V]:</b>	220 - 240	<b>Frequency [Hz]:</b>	50 - 60
<b>Electrical protection class:</b>	I	<b>Luminous efficacy [lm/W]:</b>	2.40
<b>Exchangeable source:</b>	1	<b>Light colour:</b>	violet
<b>Material of the body:</b>	carbon steel	<b>LED lifespan L70B50 [h]:</b>	9000
<b>Colour of the body:</b>	white	<b>Working temperature [°C]:</b>	from -20 to +45
<b>Dimensions (H/W/T/S) [mm]:</b>	724/160/160	<b>Operating mode:</b>	no
<b>Ingress protection:</b>	IP20	<b>Control:</b>	no
<b>Version:</b>	single-function	<b>Master/slave:</b>	no
<b>Mounting version:</b>	detached	<b>Through wiring:</b>	no
<b>Plug type:</b>	UNI-SCHUKO	<b>Protection type:</b>	mo
<b>Cable length [m]:</b>	3	<b>Number in carton box [pcs]:</b>	1
<b>Switch:</b>	1	<b>Number on the palette [pcs]:</b>	28
<b>Total power consumption [W]:</b>	82	<b>Net weight [kg]:</b>	7.150
<b>UV-C wavelength [nm]:</b>	253.70	<b>Gross weight [kg]:</b>	7.780
<b>Dust filter:</b>	1	<b>Warranty [years]:</b>	2
<b>Flow air disinfection function:</b>	1	<b>CE certificate:</b>	<a href="#">339/2023</a>
<b>Max volume of the disinfected room [m<sup>3</sup>]:</b>	60	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0317/20</a>
<b>Working time counter:</b>	1	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>HEPA filter holder:</b>	1		

# UV-C STERILON FLOW 72W MONO

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240478	Wall bracket STERILON FLOW MONO
243653	Set of guide wheels Sterilon Flow 72W gloss white
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
244339	Set of 5 x Sterilon AIR G1 3x127x135mm pre-filter



Set of guide wheels Sterilon Flow 72W  
gloss white (243653)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 339/2023