

UV-C STERILON FLOW 144W PREMIUM

DETAILED CARD



TECHNICAL PARAMETERS

Nominal power [W]:	144
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	carbon steel
Dimensions (H/W/T/S) [mm]:	724/160/220
Ingress protection:	IP20
Mounting version:	detached
Flow air disinfection function:	1
Max volume of the disinfected room [m³]:	120
Direct surface disinfection function:	1

CHARACTERISTICS

UV-C STERILON FLOW 144W PREMIUM luminaires emitting ultraviolet (UV-C) light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is available as dual-function products. The luminaire is equipped with the ECO mode, which makes it quieter.

APPLICATION

Luminaires are recommended for use in service-providing facilities (hair and beauty salons), health care facilities, hotels, restaurants, public administration, educational and care facilities.

UV-C STERILON FLOW 144W PREMIUM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	240409	Air flow in ECO mode [m3 / h]:	110
Category type:	bactericidal and virucidal lamps	Type of light:	ultraviolet UV-C
Product line:	UV-C STERILON	ECO mode:	1
Light source:	UV-C	Protection against opening:	1
Nominal power [W]:	144	Noise intensity [dB]:	44
Service life of the UV-C radiation source [h]:	9000	Noise level in ECO mode [dB]:	38
Supply voltage [V]:	220 - 240	Internal element emitting UV-C radiation [W]:	4x36
Electrical protection class:	I	EAN:	5905963240409
Exchangeable source:	1	Frequency [Hz]:	50 - 60
Material of the body:	carbon steel	Luminous efficacy [lm/W]:	4.80
Colour of the body:	white/silver	Light colour:	violet
Dimensions (H/W/T/S) [mm]:	724/160/220	LED lifespan L70B50 [h]:	9000
Ingress protection:	IP20	Working temperature [°C]:	from -20 to +45
Mounting version:	detached	Operating mode:	no
Version:	dual-purpose	Control:	yes
Plug type:	UNI-SCHUKO	Master/slave:	no
Cable length [m]:	3	Through wiring:	no
Switch:	1	Protection type:	yes
Net weight [kg]:	10.150	Number in carton box [pcs]:	1
Total power consumption [W]:	155	Number on the palette [pcs]:	20
UV-C wavelength [nm]:	253.70	Gross weight [kg]:	10.900
Dust filter:	1	Direct surface disinfection function:	1
Flow air disinfection function:	1	Illumination area at a distance of 1 m:	14
Max volume of the disinfected room [m3]:	120	Warranty [years]:	2
Working time counter:	1	CE certificate:	323/2023
HEPA filter holder:	1	Manual:	Download PDF
Air flow [m3 / h]:	200		

UV-C STERILON FLOW 144W PREMIUM

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
240492	Wall bracket STERILON FLOW 144W
243660	Set of guide wheels Sterilon Flow 144W white matt
243677	HEPA H10 filter - set of 5 only for the Flow model
WSAW347	WSAW347 - SterilOn fan dust filter 115x115 PPM 30 1pkg=3pcs
243639	UV-C protective glasses



Set of guide wheels Sterilon Flow 144W white matt (243660)



HEPA H10 filter - set of 5 only for the Flow model (243677)



UV-C protective glasses (243639)

Card creation date: 22 July 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 323/2023