CROP FUTURE LED

DETAILED CARD



TECHNICAL PARAMETERS

Light source: LED

Rated power of the luminaire [W]*: 4

Colour temperature [K]: 6500

Diffuser material: ABS

Diffuser type: transparent

Dimensions (H/W/T/S) [mm]: 255/58/45

CHARACTERISTICS

The manual LED luminaire is a proposal for people working in a car workshop, mobile service center, garage, or on a construction site. Professionals and DIY enthusiasts alike will benefit from the functionality of the LED hand-held luminaire everyone for whom good lighting is important during work or hobby. The luminaire is characterized by high durability, a strong light beam, and a long working time, which allows you to focus on the task. At the same time, the emitted light is pleasant to the eyes, and the energy-saving LED technology itself.

- Light source: 4 W COB LED + 4 W SMD LED (above)
- \bullet Lighting time: 400 lm 3,5 h, $\,$ 120 lm 10 h $\,$
- Protection class III
- \bullet The set includes a 1.5 m microUSB cable
- Ingress protection class: IP54
- Dimensions: 255x58x45 mm
- Weight: 110 g
- Battery Li-ion 3,7V 2600 mAh
- Charging time: 3 h
- \bullet Magnet on the bottom of the lamp

APPLICATION

It is used as a working luminaire for lighting workplaces, workshops, or garages.



CROP FUTURE LED

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	608599
EAN:	5905963608599
Light source:	LED
Rated power of the luminaire [W]:	4
Luminous flux [Im]:	400
Colour temperature [K]:	6500
Color rendering index (Ra) >:	80
Battery:	3.7V 2600mAh Li-ion
Battery capacity [mAh]:	2600
Surge protection [kV]:	2
Diffuser material:	ABS
Diffuser type:	transparent

Diffuser colour:	transparent
Material of the body:	ABS
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	255/58/45
Impact resistance:	IK07
Ingress protection:	IP54
Working temperature [°C]:	from -20 to +35
Net weight [kg]:	0.310
CE certificate:	278/2023
Warranty [years]:	2
Manual:	Download PDF

Card creation date: 10 March 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

