

MAGNUM BATTERY M 4050LM 840 IIIKL. 4000K (32W) BAT. 18V 2AH

DETAILED CARD



TECHNICAL PARAMETERS

Index:	249341
Ingress protection:	IP20
Impact resistance:	IK10
Nominal power [W]:	30
Colour temperature [K]:	4000
Luminous flux [lm]*:	4050
Supply voltage [V]:	18
Energy efficiency class:	D
Electrical protection class:	III
Material of the body:	PP

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC), transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. It has a switch with 4-step luminous flux control. It can be mounted on a Future Stand, significantly increasing the range and comfort of use. MAGNUM BATTERY M is also available as a set with a capacious, branded and durable battery and charger. The battery is compatible with other Bosch devices.

Battery-powered version:

Operating modes for battery-based operation:

2Ah Battery:

500 lm, working time: 9h

1850 lm, working time: 2h 30min

2750 lm, working time: 1h 30min

4050 lm, working time: 1h

5Ah Battery:

500 lm, working time: 23h

1850 lm, working time: 6h

2750 lm, working time: 4h

4050 lm, working time: 2h 30min

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

MAGNUM BATTERY M 4050LM 840 IIIKL. 4000K (32W) BAT. 18V 2AH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	30	Colour of the body:	grey
Index:	249341	Dimensions (H/W/T/S) [mm]:	205/400/82
Light source:	LED module	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP20
Luminous flux [lm]:	4050	Accessories included:	2 x 2Ah batteries; stand with CLICK function
Rated power of the luminaire [W]:	32.50	Net weight [kg]:	1.670
Battery:	Bosch 18V	Warranty [years]:	3
Battery capacity [mAh]:	2	LED lifespan L70B50 [h]:	140000
Supply voltage [V]:	18	LED lifespan L80B20 [h]:	85000
Energy efficiency class:	D	LED lifespan L90B10 [h]:	42000
Electrical protection class:	III	Light distribution type:	lambertian
Colour rendering index:	>80	Dimensions of bulk box (H/W/D) [mm]:	1190/790/980
SDCM:	≤ 3	Additional accessories:	Stand 000737
Beam angle [°]:	120	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	ETIM class:	EC000346
Diffuser colour:	transparent	Warranty [years]:	3
Optics material:	PC	CE certificate:	116/2023
Material of the body:	PP	Manual:	Download PDF

MAGNUM BATTERY M 4050LM 840 IIIKL. 4000K (32W) BAT. 18V 2AH

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
249150	ACCU BOSCH 18V 2Ah
249167	ACCU BOSCH 18V 5Ah
249174	ACCU CHARGER BOSCH EU 18V 2Ah/5Ah
249181	ACCU CHARGER BOSCH UK 18V 2Ah/5Ah



FUTURE STAND Tripod with Click
Head System (000737)

Card creation date: 26 September 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 116/2023