

# TYTAN 2 LED BASIC 1450MM 7900LM 840 IP66 AW 3H 54W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	911569
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Rated power of the luminaire [W]*:</b>	54
<b>Luminous flux [lm]*:</b>	7900
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

TYTAN 2 LED BASIC is a basic line of lighting fixtures which provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy of <math><150\text{lm/W}</math>. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of  $\pm 50$  mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation.

## APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

# TYTAN 2 LED BASIC 1450MM 7900LM 840 IP66 AW 3H 54W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	911569	<b>Ingress protection:</b>	IP66
<b>EAN:</b>	5905963911569	<b>Mounting version:</b>	surface, suspended
<b>Light source:</b>	LED module	<b>Working temperature [°C]:</b>	from 0 to +35
<b>Rated power of the luminaire [W]:</b>	54	<b>Emergency lighting [h]:</b>	3
<b>Supply voltage [V]:</b>	220 – 240	<b>Net weight [kg]:</b>	2.400
<b>Frequency [Hz]:</b>	50-60	<b>Category type:</b>	battens
<b>Luminous flux [lm]:</b>	7900	<b>Autotest:</b>	yes
<b>Luminous efficacy [lm/W]:</b>	146	<b>AC voltage range [V]:</b>	220 - 240
<b>Energy efficiency class:</b>	C	<b>LED lifespan L70B50 [h]:</b>	103000
<b>Electrical protection class:</b>	I	<b>LED lifespan L80B20 [h]:</b>	65000
<b>Colour temperature [K]:</b>	4000	<b>LED lifespan L90B10 [h]:</b>	32000
<b>Colour rendering index:</b>	>80	<b>Photobiological safety:</b>	RG0 - exempt (no photobiological hazard)
<b>SDCM:</b>	≤ 3	<b>Category of application:</b>	commercial facilities, industrial
<b>Power factor:</b>	0.95	<b>Mark D:</b>	yes
<b>Battery life [h:min]:</b>	3	<b>Control:</b>	1
<b>Exchangeable source:</b>	yes	<b>Operating mode:</b>	1
<b>Diffuser material:</b>	PC	<b>Warranty [years]:</b>	2 / 0.5 (bateria)
<b>Diffuser type:</b>	MAT	<b>CE certificate:</b>	<a href="#">274/2023</a>
<b>Material of the body:</b>	PC	<b>ENEC Certificate:</b>	<a href="#">0310/ENEC/23</a>
<b>Colour of the body:</b>	grey	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0152/20</a>
<b>Dimensions (H/W/T/S) [mm]:</b>	1432/85/80	<b>HACCP:</b>	<a href="#">852/2004</a>
<b>Mounting dimensions [mm]:</b>	970	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Impact resistance:</b>	IK09		

## TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor




wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich

# TYTAN 2 LED BASIC 1450MM 7900LM 840 IP66 AW 3H 54W

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20\*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)

Card creation date: 19 August 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 274/2023