FLATO LED L 4600LM 840 IP54 II KL. 3M WT.UNI-SCHUKO GREY (47W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK07
Rated power of the luminaire [W]*:	47
Luminous flux [lm]*:	4600
Colour temperature [K]:	4000
Energy efficiency class:	E
Material of the body:	PP
Colour of the body:	graphite
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The luminaire body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. Also equipped with a comfortable mounting arm offering wide angle adjustment.

APPLICATION

It can be used in general lighting applications: building façades, outbuildings, courtyards, in front of building entrances, billboards, advertisement boards and as a workplace luminaire for e.g. illuminating workplaces, workshops, construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

FLATO LED L 4600LM 840 IP54 II KL. 3M WT.UNI-SCHUKO GREY (47W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	622199
Light source:	LED module
Nominal power [W]:	47
Rated power of the luminaire [W]:	47
Supply voltage [V]:	220-240
Luminous flux [lm]:	4600
Energy efficiency class:	E
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	PP

Colour of the body:	graphite
Dimensions (H/W/T/S) [mm]:	236/261/64
Impact resistance:	IK07
Ingress protection:	IP54
Plug type:	UNI-SCHUKO
Cable length [m]:	3
Net weight [kg]:	1
Warranty [years]:	2
Category type:	floodlights, workplace floodlights
Manual:	Download PDF
CE certificate:	188/2023

Card creation date: 02 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 188/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl