

FLATO LED L 4600LM 850 IP54 II KL. 3M WT.UNI-SCHUKO GREY (47W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK07
Rated power of the luminaire [W]*:	47
Luminous flux [lm]*:	4600
Colour temperature [K]:	5000
Energy efficiency class:	E
Material of the body:	PP
Colour of the body:	graphite
Diffuser material:	PC
Diffuser type:	OPAL

CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The luminaire body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. Also equipped with a comfortable mounting arm offering wide angle adjustment.

APPLICATION

It can be used in general lighting applications: building façades, outbuildings, courtyards, in front of building entrances, billboards, advertisement boards and as a workplace luminaire for e.g. illuminating workplaces, workshops, construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

FLATO LED L 4600LM 850 IP54 II KL. 3M WT.UNI-SCHUKO GREY (47W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	47	Dimensions (H/W/T/S) [mm]:	236/261/64
Index:	622250	Colour of the body:	graphite
Light source:	LED module	Impact resistance:	IK07
Colour temperature [K]:	5000	Ingress protection:	IP54
Nominal power [W]:	47	Plug type:	UNI-SCHUKO
Luminous flux [lm]:	4600	Cable length [m]:	3
Diffuser type:	OPAL	Net weight [kg]:	1
Supply voltage [V]:	220-240	Warranty [years]:	2
Energy efficiency class:	E	Category type:	floodlights, workplace floodlights
Diffuser material:	PC	Manual:	Download PDF
Material of the body:	PP	CE certificate:	188/2023

Card creation date: 02 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 188/2023