

# FLATO LED M 1750LM 850 IP54 II KL. 3M WT.UNI-SCHUKO GREY (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	622076
<b>Ingress protection:</b>	IP54
<b>Impact resistance:</b>	IK08
<b>Rated power of the luminaire [W]*:</b>	17
<b>Luminous flux [lm]*:</b>	1750
<b>Colour temperature [K]:</b>	5000
<b>Material of the body:</b>	PP
<b>Colour of the body:</b>	graphite
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL

## CHARACTERISTICS

Compact LED floodlight ensuring even and stable directional lighting. The body, made of copolymer with rubber, increases its durability. The luminaire is equipped with anti-glare diffuser made of frosted PC with an UV stabiliser, which, despite the matt surface, transmits up to 80% of the light emitted by the diodes.

## APPLICATION

It can be used in general lighting applications: building façades, outbuildings, courtyards, in front of building entrances, billboards, advertisement boards and as a workplace luminaire for e.g. illuminating workplaces, workshops, construction sites. The smaller size and compact design make it more convenient to transport. The luminaire is designed for outdoor use, industrial applications or other applications where the lighting standards allow CRI <80.

# FLATO LED M 1750LM 850 IP54 II KL. 3M WT.UNI-SCHUKO GREY (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	622076	Colour of the body:	graphite
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	132/185/74
Rated power of the luminaire [W]:	17	Impact resistance:	IK08
Nominal power [W]:	17	Ingress protection:	IP54
Supply voltage [V]:	220-240	Plug type:	UNI-SCHUKO
Luminous flux [lm]:	1750	Cable length [m]:	3
Colour temperature [K]:	5000	Category type:	floodlights, workplace floodlights
Beam angle [°]:	120	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	CE certificate:	<a href="#">186/2023</a>
Diffuser type:	OPAL	Energy efficiency class:	E
Material of the body:	PP	ETIM class:	EC001744

Card creation date: 02 September 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 186/2023