# BARIS 52 LED P GK 1145MM 1400LM 840 IP44/IP20 I CL. UGR ANODE CO 15W

**DETAILED CARD** 





# **TECHNICAL PARAMETERS**

Ingress protection: IP44/IP20

Rated power of the luminaire [W]\*: 15

Luminous flux [lm]\*: 1400

Colour temperature [K]: 4000

Energy efficiency class:

Material of the body: aluminium

Colour of the body: grey

Diffuser material: PC

Diffuser type: UGR

Mounting version: flush-mounted in plasterboard ceilings

# **CHARACTERISTICS**

Recessed lighting luminaire of classic proportions and modern design intended for installation in plaster-cardboard ceilings. Luminaire construction allows for installation in ceilings with two-level cross grid without breaching main (top) profiles. It is possible due to appropriately selected height of the lamp profile, reduced to 37mm and separate box for the power supply, which can be placed next to the luminaire. The luminaire is offered in four lengths with the possibility to combine into a line with a constant flux ratio from the meter (system available on request). Luminaire body is made of anodized aluminum profile in grey or reluminum profile painted white or black (other colors available on request). The optical system is in the form of a dedicated, flexible opal diffuser uniformly illuminating the luminaire, with a PRM prismatic diffuser or with a louver meeting the stringent requirements regarding glare UGR<19. The luminaire comes with a complete mounting system for a quick and easy installation in plasterboard ceilings.

# **APPLICATION**

The luminaire is dedicated for indoor use. It is applied as the source of the main light and conducive to office work requiring concentration of eyesight. Classic design, energy-saving LED modules and the possibility of cooperation with external lighting control systems in the DALI standard dedicate the lamp to be used in modern office buildings of the A+ class, with particular consideration of representative rooms, conference halls, passageways and everywhere, where a low glare and/or high IP44 sealing from below is required.



# BARIS 52 LED P GK 1145MM 1400LM 840 IP44/IP20 I CL. UGR ANODE CO 15W


**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Index:	927270
EAN:	5905963927270
Rated power of the luminaire [W]:	15
Luminous flux [lm]:	1400
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	98
Energy efficiency class:	F
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	109 000
LED lifespan L80B20 [h]:	69 000
LED lifespan L90B10 [h]:	34000
Exchangeable source:	yes
Diffuser material:	PC

	•
Diffuser type:	UGR
Diffuser colour:	transparent
Optics:	raster
Material of the body:	aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	37/69/1145
Ingress protection:	IP44/IP20
Mounting version:	flush-mounted in plasterboard ceilings
Net weight [kg]:	1.980
UGR (4H8H):	<19
Impact resistance:	IK03
Working temperature [°C]:	from -25 to +35
CE certificate:	<u>235/2023</u>
PZH certificate:	B-BK-60112-0357/2023
Manual:	Download PDF
Plik LDT:	Download

# **LIGHT CURVES**



Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



