## **OVAL LED**

**GENERAL CARD** 





### **TECHNICAL PARAMETERS**

Ingress protection:	IP44/40

Impact resistance: IK06

Nominal power [W]: 2.50

**Luminous flux [lm]\*:** 210 - 210

Colour temperature [K]: 3000; 4000

Energy efficiency class: G

Material of the body: PP

**Diffuser material:** glass

**Diffuser type:** PRM

**Mounting version:** surface

**Dimensions (H/W/T/S) [mm]:** 125/170/105;

### **CHARACTERISTICS**

Surface-mounted, oval channel-type LED fitting with ingress protection class IP44 and an integrated energy-saving light source LED. Polypropylene base; prismatic glass diffuser. Fitting is available in two power versions and six base colors. Also available are numerous special-purpose versions: a 24V fitting or fittings that can be used as marker lights (Oval LED RED equipped with red-colored diodes and Oval LED BLUE equipped with blue-colored diodes).

#### **APPLICATION**

Surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial façade lighting, parking lots). The 24V version is particularly well-suited to be used as a light source for public rooms and buildings (civic buildings, apartment buildings).



# **OVAL LED**

GENERAL CARD

### **AVAILABLE VERSIONS**



Click index >>, to see details


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Colour of the body	Energy efficiency class	Index
2.50	3000	210	PRM	white	G	<u>&gt;&gt; 233081</u>
2.50	4000	210	PRM	white	G	<u>&gt;&gt; 233012</u>
2.50	3000	210	PRM	gray	G	<u>&gt;&gt; 233135</u>
2.50	4000	210	PRM	gray	G	<u>&gt;&gt; 233067</u>



## **OVAL LED**

GENERAL CARD

### **LUMINOUS INTENSITY DISTRIB. CURVE**



Oval LED 3W

Card creation date: 19 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



