



TECHNICAL PARAMETERS

Warranty [years]:	2 / 0.5 (bateria)
Ingress protection:	IP65
Impact resistance:	IK07
Nominal power [W]:	1.00; 2.00
Luminous flux [lm]*:	130 - 260
Colour temperature [K]:	5000
Colour rendering index:	70
Electrical protection class:	II
Material of the body:	PC
Light distribution type:	corridor; general; open space
Diffuser material:	PMMA
Battery:	NiMh
Autotest:	tak
Working temperature [°C]:	from +5 to +35; from -19 to +35
Mounting version:	surface
CNBOP certificate:	4958/2023
Energy efficiency class:	C; D

CHARACTERISTICS

Surface-mounted autonomous emergency luminaire with integrated, energy-saving LED light panel. Body made of polycarbonate (PC). Optical system available in 3 variants: basic, corridor, open space. Luminaire is fitted with batteries with 1h, 2h or 3h emergency operation time. The luminaire is using Ni-Mh or Ni-Cd battery with voltage of 3.6V and 24 hours of full charge with manual or automatic test function (AT).

Available versions:
M – maintained,
NM- non-maintained,
AT – autotest.

APPLICATION

Autonomous emergency luminaire is mainly used for illumination of escape routes and fire protection devices after power failure, i.e. in emergency mode. Especially recommended everywhere, where it is necessary to install emergency lighting within the scope of modernization of existing system. Successfully replaces luminaires with embedded emergency module. Due to additional sealing, the luminaire achieves IP65 tightness and may be used in places with increased humidity or outdoors under the roofing.

AVAILABLE VERSIONS



Click index >>, to see details

DOT CS LED corridor

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Emergency lighting [h]	Light distribution type	Operating mode	Autotest	Working temperature [°C]	Energy efficiency class	Index
1	5000	140	1	corridor	NM	yes	from +5 to +35	C	>> 550201
1	5000	140	2	corridor	NM	yes	from +5 to +35	C	>> 550263
1	5000	140	3	corridor	NM	yes	from +5 to +35	C	>> 550324
2	5000	260	1	corridor	NM	yes	from +5 to +35	D	>> 550218
2	5000	260	2	corridor	NM	yes	from +5 to +35	D	>> 550270
2	5000	260	3	corridor	NM	yes	from +5 to +35	D	>> 550331


DOT CS LED general

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Emergency lighting [h]	Light distribution type	Operating mode	Autotest	Working temperature [°C]	Energy efficiency class	Index
1	5000	130	1	general	NM	yes	from +5 to +35	D	>> 550027
1	5000	130	2	general	NM	yes	from +5 to +35	D	>> 550089
1	5000	130	3	general	NM	yes	from +5 to +35	D	>> 550140
1	5000	130	3	general	NM	yes	from -19 to +35	D	>> 551154
2	5000	250	1	general	NM	yes	from +5 to +35	D	>> 550034
2	5000	250	2	general	NM	yes	from +5 to +35	D	>> 550096
2	5000	250	3	general	NM	yes	from +5 to +35	D	>> 550157


DOT CS LED open space

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Emergency lighting [h]	Light distribution type	Operating mode	Autotest	Working temperature [°C]	Energy efficiency class	Index
1	5000	140	1	open space	NM	yes	from +5 to +35	C	>> 550386
1	5000	140	2	open space	NM	yes	from +5 to +35	C	>> 550447
1	5000	140	3	open space	NM	yes	from +5 to +35	C	>> 550508
2	5000	260	1	open space	NM	yes	from +5 to +35	D	>> 550393
2	5000	260	2	open space	NM	yes	from +5 to +35	D	>> 550454
2	5000	260	3	open space	NM	yes	from +5 to +35	D	>> 550515


LUMINOUS INTENSITY DISTRIB. CURVE



DOT CR LED 2W 250lm NM AT
(ogólny)




DOT CRC LED 2W 260lm NM AT
(korytarzowy)




DOT CRO LED 2W 260lm NM AT
(open space)

ACCESSORIES AVAILABLE

index	Name
997570	DOT square frame. white matt texture
997587	DOT square frame black matt texture
551161	Ceiling spacer DOT white matt
	DOT CS galvanized steel arm



DOT square frame. white matt texture (997570)



DOT square frame black matt texture (997587)



Ceiling spacer DOT white matt (551161)



DOT CS galvanized steel arm (545672)