



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK06
Nominal power [W]:	23.00 - 30.00
Luminous flux [lm]*:	3350; 4400
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	II
Energy efficiency class:	D
Material of the body:	PC
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	surface, suspended
Warranty [years]:	2

CHARACTERISTICS

MIMO LED represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED modules offering the best lighting level required and energy savings of up to 66%. The multilayer shade has been made of UV-resistant polycarbonate.

APPLICATION

The multifunctional LED luminaire is designed for use in areas with increased dust and humidity. It is particularly suitable for industrial conditions, car parks (underground and multi-storey ones), sports stadiums, warehouses, transport terminals and underground passages. The luminaire is used both in new applications, as well as in replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended installation using standard equipment.

MIMO LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

MIMO LED 1230/55/35mm


Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Through wiring	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
23	4000	3350	OPAL		1230/55/35	D	>> 100963
23	4000	3350	OPAL	LS2	1230/55/35	D	>> 100970

MIMO LED 1510/55/35mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Through wiring	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
30	4000	4400	OPAL		1510/55/35	D	>> 100987

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



MIMO DOB LED