



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	35.00; 70.00
<b>Luminous flux [lm]*:</b>	4300 - 9300
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	D; E
<b>Material of the body:</b>	steel
<b>Colour of the body:</b>	white
<b>Optics material:</b>	PMMA
<b>Optics:</b>	lens
<b>Mounting version:</b>	recessed; surface, suspended
<b>Supply voltage [V]:</b>	220-240
<b>Frequency [Hz]:</b>	50 - 60
<b>Dimensions (H/W/T/S) [mm]:</b>	85/1435/60;

## CHARACTERISTICS

The surface, recessed or suspended (suspension system as accessories) mounted fixture equipped with energy-saving LED panels and a lens generating asymmetric light distribution. It was made of a powder-coated white RAL 9003 steel sheet. Shade – a PMMA iridescent lens of 85% light transmission assures high efficiency of the fixture. Available in two power options: 35W with a single LED Panel and 70W with a double LED panel. Colour temperature: 3000K or 4000K. The fixture's colour rendering index is CRI>80 and standard deviation colour matching (SDCM): ≤ 3, assuring homogeneity and uniformity of light. Suspension of the luminaire is possible, thanks to a special suspension system (accessories).

## APPLICATION

The fixture is equipped with linear lenses assuring asymmetric distribution with a beam angle of 20° that is perfect for illumination of boards, paintings and display cases. An iridescent lampshade disperses light assuring that objects are uniformly illuminated with no light reflex. The fixture is applied mostly in schools, universities, museums and art galleries.

## AVAILABLE VERSIONS



Click index >>, to see details


### TABLO LED surface, suspended

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	Index
35	3000	4300	E	<a href="#">&gt;&gt; 514869</a>
35	4000	4650	D	<a href="#">&gt;&gt; 514876</a>
70	3000	8650	E	<a href="#">&gt;&gt; 514821</a>
70	4000	9300	D	<a href="#">&gt;&gt; 514838</a>

### TABLO LED recessed

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Energy efficiency class	Index
35	3000	4300	E	<a href="#">&gt;&gt; 514883</a>
35	4000	4650	D	<a href="#">&gt;&gt; 514890</a>
70	3000	8650	E	<a href="#">&gt;&gt; 514845</a>
70	4000	9300	D	<a href="#">&gt;&gt; 514852</a>

LUMINOUS INTENSITY DISTRIB. CURVE



TABLO LED

ACCESSORIES AVAILABLE

index	Name
171512	SINGLE SUSPENDE D CORD
171642	SINGLE SUSPENDE D CORD (SQUARE BOX)
171635	SINGLE SUSPENDE D CORD (ROUND BOX)
171703	SINGLE ELECTRICAL SUSPENDE D CORD (ROUND BOX) TABLO NT
171710	SINGLE ELECTRICAL SUSPENDE D CORD (SQUARE BOX) TABLO NT



SINGLE SUSPENDE D CORD (171512)



SINGLE SUSPENDE D CORD (SQUARE BOX) (171642)



SINGLE SUSPENDE D CORD (ROUND BOX) (171635)



SINGLE ELECTRICAL SUSPENDE D CORD (ROUND BOX) TABLO NT (171703)



SINGLE ELECTRICAL SUSPENDE D CORD (SQUARE BOX) TABLO NT (171710)