

NECTRA S LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	12.00 - 26.00
Luminous flux [lm]*:	850 - 2200

CHARACTERISTICS

Surface-mounted downlight luminaire equipped with energy-saving LED light source. Body made of white powder-coated aluminium ensures optimal conditions for the LED operation . The diffuser is made of highly transparent PMMA to guarantee high luminous flux. Colour temperature 3000K, 4000K; CRI>80.

APPLICATION

The surface mounted luminaire is intended for indoor use: in offices, passageways, general utility rooms. Due to the high energy saving and even light distribution on the surface, it is recommended for use in public buildings.

NECTRA S LED

GENERAL CARD

AVAILABLE VERSIONS




Click index >>, to see details

NECTRA S LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



nectra s led 18W 4000K

Card creation date:18 November 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric andelectronic waste equipment regulations (WEEE).



Certificate CE - Nr: 43/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl