

PIATTO 610

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	28.00; 45.00
Luminous flux [lm]*:	2050 - 3200
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	F; G
Material of the body:	powder coated aluminium
Colour of the body:	black and gold; black-silver; white-gold
Diffuser material:	PMMA
Diffuser type:	OPAL
Mounting version:	surface; suspended
Dimensions (H/W/T/S) [mm]:	ø610/150; ø610/150/1500;
Warranty [years]:	5

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. Possibility of surface and suspended mounting allows various applications. The integrated energy-saving LED panel ensures high light quality and long-term trouble-free use. Optionally, there are versions equipped with a microwave motion sensor (RCR) and the possibility of control via the DALI protocol, increasing the energy-saving and functional properties of the luminaires.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO 610

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

PIATTO 610 surface

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Motion sensor	DIMM DALI	Colour of the body	Energy efficiency class	Index
28	3000	2050			white-gold	G	>> 670022
28	4000	2200			white-gold	F	>> 670053
28	3000	2050	yes		white-gold	G	>> 670206
28	4000	2200	yes		white-gold	F	>> 670237
28	3000	2050			black-silver	G	>> 670015
28	4000	2200			black-silver	F	>> 670046
28	3000	2050	yes		black-silver	G	>> 670190
28	4000	2200	yes		black-silver	F	>> 670220
28	3000	2050			black and gold	G	>> 670008
28	4000	2200			black and gold	F	>> 670039
28	3000	2050	yes		black and gold	G	>> 670183
28	4000	2200	yes		black and gold	F	>> 670213
45	3000	2950			white-gold	G	>> 670084
45	4000	3200			white-gold	G	>> 670114
45	3000	2950		yes	white-gold	G	>> 670145
45	4000	3200		yes	white-gold	G	>> 670176
45	3000	2950	yes		white-gold	G	>> 670268
45	4000	3200	yes		white-gold	G	>> 670299
45	3000	2950			black-silver	G	>> 670077
45	4000	3200			black-silver	G	>> 670107
45	3000	2950		yes	black-silver	G	>> 670138
45	4000	3200		yes	black-silver	G	>> 670169
45	3000	2950	yes		black-silver	G	>> 670251
45	4000	3200	yes		black-silver	G	>> 670282
45	3000	2950			black and gold	G	>> 654657
45	4000	3200			black and gold	G	>> 670091
45	3000	2950		yes	black and gold	G	>> 670121
45	4000	3200		yes	black and gold	G	>> 670152
45	3000	2950	yes		black and gold	G	>> 670244
45	4000	3200	yes		black and gold	G	>> 670275

PIATTO 610 suspended

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Motion sensor	DIMM DALI	Colour of the body	Energy efficiency class	Index
28	3000	2050			white-gold	G	>> 670336

PIATTO 610

GENERAL CARD

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Motion sensor	DIMM DALI	Colour of the body	Energy efficiency class	Index
28	4000	2200			white-gold	F	>> 670374
28	3000	2050			black-silver	G	>> 670312
28	4000	2200			black-silver	F	>> 670367
28	3000	2050			black and gold	G	>> 670305
28	4000	2200			black and gold	F	>> 670343
28	3000	2050		yes	black and gold	G	>> 654718
45	3000	2950			white-gold	G	>> 670404
45	4000	3200			white-gold	G	>> 670435
45	3000	2950		yes	white-gold	G	>> 670466
45	4000	3200		yes	white-gold	G	>> 670497
45	3000	2950			black-silver	G	>> 670398
45	4000	3200			black-silver	G	>> 670428
45	3000	2950		yes	black-silver	G	>> 670459
45	4000	3200		yes	black-silver	G	>> 670480
45	3000	2950			black and gold	G	>> 670381
45	4000	3200			black and gold	G	>> 670411
45	3000	2950		yes	black and gold	G	>> 654664
45	4000	3200		yes	black and gold	G	>> 654671

Card creation date: 19 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 220/2023; 83/2020