

PIATTO 340

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Nominal power [W]:	9.00
Luminous flux [lm]*:	520 - 560
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
Energy efficiency class:	G
Material of the body:	powder coated aluminium
Colour of the body:	black-gold; black-silver; white-gold
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	suspended
Dimensions (H/W/T/S) [mm]:	ø340/280/1500;

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. The integrated energy-saving LED panel ensures high light quality and long-term trouble-free use.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.

PIATTO 340

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

PIATTO 340 suspended

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Colour of the body	Energy efficiency class	Index
9	3000	520	white-gold	G	>> 654145
9	4000	560	white-gold	G	>> 654107
9	3000	520	black-silver	G	>> 654220
9	4000	560	black-silver	G	>> 654183
9	3000	520	black-gold	G	>> 654060
9	4000	560	black-gold	G	>> 654022

Card creation date: 31 March 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 60/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl