GENERAL CARD





TECHNICAL PARAMETERS

Ingress protection: IP20

Nominal power [W]: 9.00

Luminous flux [lm]*: 520 - 560

Colour temperature [K]: 3000; 4000

Color rendering index (Ra) >: 80

Energy efficiency class: G

Material of the body: powder coated aluminium

Colour of the body: black-gold; black-silver;

white-gold

Diffuser material: PC

Diffuser type: OPAL

Mounting version: suspended

Dimensions (H/W/T/S) [mm]: ø340/280/1500;

CHARACTERISTICS

The PIATTO line of luminaires is distinguished by its elegant design that allows it to be used in a variety of arrangements. The minimalist aluminum shades, available as standard in three fashionable color schemes, will emphasize the ambience of every interior, creating a strong decorative accent. The integrated energy-saving LED panel ensures high light quality and long-term trouble-free use.

APPLICATION

A lightweight, suspended or surface-mounted PIATTO luminaire will brighten up rooms that are to stand out with their aesthetics. It can be used in public areas, such as restaurants and hotels, as well as in private apartments.



PIATTO 340

GENERAL CARD

AVAILABLE VERSIONS



PIATTO 340 suspended

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Colour of the body	Energy efficiency class	Index
9	3000	520	white-gold	G	<u>>> 654145</u>
9	4000	560	white-gold	G	<u>>> 654107</u>
9	3000	520	black-silver	G	<u>>> 654220</u>
9	4000	560	black-silver	G	<u>>> 654183</u>
9	3000	520	black-gold	G	<u>>> 654060</u>
9	4000	560	black-gold	G	>> 654022

