

# CORAL LED EVO PLUS

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Light source:</b>	LED module
<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	9.00
<b>Luminous flux [lm]*:</b>	740 - 810
<b>Colour temperature [K]:</b>	3000; 4000
<b>Colour rendering index:</b>	>80
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	F; G
<b>Material of the body:</b>	PP
<b>Ring material:</b>	PP
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL
<b>Optics material:</b>	PMMA
<b>Mounting version:</b>	recessed; surface
<b>Dimensions (H/W/T/S) [mm]:</b>	ø260/108;

## CHARACTERISTICS

Ceiling lights for ceiling or wall mounting. Luminaire design allows surface and concealed installation. The unique design allows replacement of the LED GO! (light source) module without having to replace the entire luminaire. Integrated design for easy installation. Surface-mounted luminaire allows cable termination.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:  
- with a radio motion sensor.

## APPLICATION

Suspended mounting board allows quick installation. Removable mounting board available on request as a service kit. Surface wiring. Holes for connection with surface installation, through-wiring possible.

# CORAL LED EVO PLUS

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### CORAL LED EVO PLUS surface

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Energy efficiency class	Index
9	3000	740	OPAL		F	<a href="#">&gt;&gt; 223655</a>
9	4000	810	OPAL		F	<a href="#">&gt;&gt; 223679</a>
9	3000	740	OPAL	yes	F	<a href="#">&gt;&gt; 223662</a>
9	4000	810	OPAL	yes	F	<a href="#">&gt;&gt; 223686</a>

### CORAL LED EVO PLUS recessed

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Energy efficiency class	Index
9	3000	740	OPAL		F	<a href="#">&gt;&gt; 223716</a>
9	4000	810	OPAL		F	<a href="#">&gt;&gt; 223730</a>
9	3000	740	OPAL	yes	G	<a href="#">&gt;&gt; 223723</a>
9	4000	810	OPAL	yes	F	<a href="#">&gt;&gt; 223747</a>



# CORAL LED EVO PLUS

GENERAL CARD

## ACCESSORIES AVAILABLE

index	Name
<a href="#">223778</a>	CORAL LED EVO PLUS 830 - SERVICE KIT
<a href="#">223792</a>	CORAL LED EVO PLUS 830 RCR - SERVICE KIT
<a href="#">223785</a>	CORAL LED EVO PLUS 840 - SERVICE KIT
<a href="#">223808</a>	CORAL LED EVO PLUS 840 RCR - SERVICE KIT

Card creation date: 09 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 74/2018



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl