

CORAL LED EVO

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|------------|
| Ingress protection: | IP44 |
| Nominal power [W]: | 9.00 |
| Luminous flux [lm]*: | 690 - 750 |
| Colour temperature [K]: | 3000; 4000 |
| Energy efficiency class: | F; G |
| Material of the body: | PP |
| Ring material: | PP |
| Diffuser material: | PC |
| Diffuser type: | OPAL |
| Optics material: | PMMA |
| Mounting version: | recessed |
| Dimensions (H/W/T/S) [mm]: | ø260/108; |

CHARACTERISTICS

Ceiling lights for ceiling or wall mounting. Luminaire design allows surface and concealed installation. The unique design allows replacement of the LED GO! (light source) module without having to replace the entire luminaire. Integrated design for easy installation. Surface-mounted luminaire allows cable termination.

APPLICATION

Suspended mounting board allows quick installation. Removable mounting board available on request as a service kit. Surface wiring. Holes for connection with surface installation, through-wiring possible.

CORAL LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details


CORAL LED EVO recessed

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | Motion sensor | Index |
|-------------------|------------------------|---------------------|---------------|---------------|---------------------------------|
| 9 | 3000 | 690 | OPAL | | >> 223907 |
| 9 | 4000 | 750 | OPAL | | >> 223921 |
| 9 | 3000 | 690 | OPAL | yes | >> 223914 |
| 9 | 4000 | 750 | OPAL | yes | >> 223938 |

CORAL LED EVO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



CORAL LED

CORAL LED EVO

GENERAL CARD

ACCESSORIES AVAILABLE

| index | Name |
|------------------------|-------------------------------------|
| 223969 | CORAL LED EVO 830 - SERVICE KIT |
| 223983 | CORAL LED EVO 830 RCR - SERVICE KIT |
| 223976 | CORAL LED EVO 840 - SERVICE KIT |
| 223990 | CORAL LED EVO 840 RCR - SERVICE KIT |

Card creation date: 09 November 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 73/2018



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl