

NECTRA LED IP44

GENERAL CARD



TECHNICAL PARAMETERS

| | |
|-----------------------------------|-------------------|
| Ingress protection: | IP44/20 |
| Nominal power [W]: | 9.00 - 9.00 |
| Luminous flux [lm]*: | 690 - 690 |
| Colour temperature [K]: | 3000 |
| Colour rendering index: | >80 |
| Energy efficiency class: | F |
| Material of the body: | PC, aluminium |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |
| Mounting version: | recessed |
| Working temperature [°C]: | from -15 to +35 |
| Supply voltage [V]: | 220-240 |
| Frequency [Hz]: | 50 - 60 |
| Dimensions (H/W/T/S) [mm]: | ø121/67; |
| PZH certificate: | HK/K/1055/06/2017 |

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings. Available in three power versions and two colour options

NECTRA LED IP44

GENERAL CARD

AVAILABLE VERSIONS




Click index >>, to see details

| Nominal power [W] | Colour temperature [K] | Luminous flux [lm]* | Diffuser type | DIMM DALI | Dimensions (H/W/T/S) [mm] | Energy efficiency class | Index |
|-------------------|------------------------|---------------------|---------------|-----------|---------------------------|-------------------------|---------------------------------|
| 9 | 3000 | 690 | OPAL | | ø121/67 | F | >> 059926 |

NECTRA LED IP44

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



NECTRA LED IP44 25W

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 19/2018; 95/2017



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl