

PROXIMA LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	24.00
Luminous flux [lm]*:	2150 - 2300
Colour temperature [K]:	3000; 4000; 6000
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	ø390/95;
Warranty [years]:	5

CHARACTERISTICS

Surface-mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details


PROXIMA LED 24W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Corridor function	Motion sensor	DIMM DALI	Emergency lighting [h]	Autotest	Vandalproof	Index
24	3000	2150	OPAL				1			>> 546068
24	3000	2150	OPAL				3			>> 546082
24	3000	2150	OPAL		yes		3	yes		>> 546235
24	3000	2150	OPAL	yes	yes	yes	3	yes		>> 546761/PA
24	3000	2150	OPAL							>> 311406/PA
24	3000	2150	OPAL		yes					>> 311949/PA
24	3000	2150	OPAL							>> 546471/PA
24	3000	2150	OPAL			yes				>> 310911/PA
24	3000	2150	OPAL		yes					>> 546488/PA
24	4000	2300	OPAL				1			>> 546006
24	4000	2300	OPAL				1	yes		>> 546037
24	4000	2300	OPAL				2	yes		>> 546044
24	4000	2300	OPAL				3			>> 546020
24	4000	2300	OPAL		yes		1			>> 546129
24	4000	2300	OPAL		yes		3			>> 546143
24	4000	2300	OPAL		yes		3	yes		>> 546174
24	4000	2300	OPAL	yes	yes	yes	3	yes		>> 546778/PA
24	4000	2300	OPAL							>> 311420/PA
24	4000	2300	OPAL		yes					>> 311918/PA
24	4000	2300	OPAL						yes	>> 310898/PA
24	4000	2300	OPAL							>> 546457/PA
24	4000	2300	OPAL			yes				>> 310928/PA
24	4000	2300	OPAL		yes				yes	>> 310850/PA
24	6000	2300	OPAL							>> 546495/PA

PROXIMA LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



PROXIMA LED 24W 4000K

Card creation date: 19 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 387/2023; 47/2017; 62/2013; 94/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl