PROXIMA LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65/54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	12.00 - 31.00
Luminous flux [lm]*:	1350 - 3550
Colour temperature [K]:	3000; 4000
Energy efficiency class:	E
Material of the body:	PP
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	ø390/110;
Warranty [years]:	5
SDCM:	3
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

PROXIMA LED

GENERAL CARD

AVAILABLE VERSIONS

Click index >>, to see details

PROXIMA LED 12W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
12	3000	1350	OPAL		>> 103995
12	3000	1350	OPAL	yes	>> 103919
12	4000	1400	OPAL		>> 103957
12	4000	1400	OPAL	yes	>> 103872

PROXIMA LED 16W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
16	3000	1700	OPAL		>> 103988
16	3000	1700	OPAL	yes	>> 103902
16	4000	1800	OPAL		>> 103940
16	4000	1800	OPAL	yes	>> 103865

PROXIMA LED 20W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
20	3000	2150	OPAL		>> 103971
20	3000	2150	OPAL	yes	>> 103896
20	4000	2200	OPAL		>> 103933
20	4000	2200	OPAL	yes	>> 103858

PROXIMA LED 22W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
22	3000	2250	OPAL		>> 103964
22	3000	2250	OPAL	yes	>> 103889
22	4000	2400	OPAL		>> 103926
22	4000	2400	OPAL	yes	>> 103841

PROXIMA LED 23W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
23	3000	2550	OPAL		>> 104107
23	3000	2550	OPAL	yes	>> 104145
23	4000	2650	OPAL		>> 104022
23	4000	2650	OPAL	yes	>> 104053

PROXIMA LED 27W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
27	3000	2950	OPAL		>> 104114

PROXIMA LED

GENERAL CARD

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
27	3000	2950	OPAL	yes	>> 104152
27	4000	3100	OPAL		>> 104039
27	4000	3100	OPAL	yes	>> 104077


PROXIMA LED 31W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Motion sensor	Index
31	3000	3400	OPAL		>> 104121
31	3000	3400	OPAL	yes	>> 104169
31	4000	3550	OPAL		>> 104046
31	4000	3550	OPAL	yes	>> 104084

PROXIMA LED

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



PROXIMA LED 24W 4000K

Card creation date: 29 October 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: max 387/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl