

# PROXIMA LED

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65/54
<b>Impact resistance:</b>	IK10
<b>Nominal power [W]:</b>	24.00
<b>Luminous flux [lm]*:</b>	2150 - 2300
<b>Colour temperature [K]:</b>	3000; 4000; 6000
<b>Energy efficiency class:</b>	F
<b>Material of the body:</b>	PP
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL
<b>Mounting version:</b>	surface
<b>Dimensions (H/W/T/S) [mm]:</b>	ø390/95;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

Surface-mounted, round LED light fixture, high ingress protection class IP65 and an integrated energy-saving light source LED. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact-resistant PC ensures the highest impact resistance of the fitting (IK10). Optional equipment: radio motion sensor (RCR).

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms. The luminaire will also work well as a general light source due to the decorative effect that it provides (indirect light distribution on the mounting surface). Two ring colors available: white or silver.

# PROXIMA LED

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details


### PROXIMA LED 24W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Corridor function	Motion sensor	DIMM DALI	Emergency lighting [h]	Autotest	Vandalproof	Index
24	3000	2150	OPAL				1			<a href="#">&gt;&gt; 546068</a>
24	3000	2150	OPAL				3			<a href="#">&gt;&gt; 546082</a>
24	3000	2150	OPAL		yes		3	yes		<a href="#">&gt;&gt; 546235</a>
24	3000	2150	OPAL	yes	yes	yes	3	yes		<a href="#">&gt;&gt; 546761/PA</a>
24	3000	2150	OPAL							<a href="#">&gt;&gt; 311406/PA</a>
24	3000	2150	OPAL		yes					<a href="#">&gt;&gt; 311949/PA</a>
24	3000	2150	OPAL							<a href="#">&gt;&gt; 546471/PA</a>
24	3000	2150	OPAL			yes				<a href="#">&gt;&gt; 310911/PA</a>
24	3000	2150	OPAL		yes					<a href="#">&gt;&gt; 546488/PA</a>
24	4000	2300	OPAL				1			<a href="#">&gt;&gt; 546006</a>
24	4000	2300	OPAL				1	yes		<a href="#">&gt;&gt; 546037</a>
24	4000	2300	OPAL				2	yes		<a href="#">&gt;&gt; 546044</a>
24	4000	2300	OPAL				3			<a href="#">&gt;&gt; 546020</a>
24	4000	2300	OPAL		yes		1			<a href="#">&gt;&gt; 546129</a>
24	4000	2300	OPAL		yes		3			<a href="#">&gt;&gt; 546143</a>
24	4000	2300	OPAL		yes		3	yes		<a href="#">&gt;&gt; 546174</a>
24	4000	2300	OPAL	yes	yes	yes	3	yes		<a href="#">&gt;&gt; 546778/PA</a>
24	4000	2300	OPAL							<a href="#">&gt;&gt; 311420/PA</a>
24	4000	2300	OPAL		yes					<a href="#">&gt;&gt; 311918/PA</a>
24	4000	2300	OPAL						yes	<a href="#">&gt;&gt; 310898/PA</a>
24	4000	2300	OPAL							<a href="#">&gt;&gt; 546457/PA</a>
24	4000	2300	OPAL			yes				<a href="#">&gt;&gt; 310928/PA</a>
24	4000	2300	OPAL		yes				yes	<a href="#">&gt;&gt; 310850/PA</a>
24	6000	2300	OPAL							<a href="#">&gt;&gt; 546495/PA</a>

# PROXIMA LED

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



PROXIMA LED 24W 4000K

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 387/2023; 47/2017; 62/2013; 94/2019



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl