

# COMPACT LED EVO P IP65

GENERAL CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65/20
<b>Impact resistance:</b>	IK07
<b>Nominal power [W]:</b>	24.00 - 60.00
<b>Luminous flux [lm]*:</b>	2750 - 8100
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	C; D; E
<b>Material of the body:</b>	ABS
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL; PRM
<b>Mounting version:</b>	recessed
<b>Dimensions (H/W/T/S) [mm]:</b>	71/595/595/0;
<b>Warranty [years]:</b>	5

## CHARACTERISTICS

Compact LED luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED panels and an evenly highlighted opal diffuser, providing low glare (UGR<19)\*. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

\* The UGR coefficient is met for the typical use of the luminaire

## APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions. The fitting's design is suitable for mounting in 600x600 modular ceilings.

# COMPACT LED EVO P IP65

GENERAL CARD

## AVAILABLE VERSIONS



Click index >>, to see details

### COMPACT LED EVO P IP65 24W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Index
24	3000	2750	OPAL		II	<a href="#">&gt;&gt; 631061</a>
24	4000	2950	OPAL		II	<a href="#">&gt;&gt; 631078</a>
24	3000	3300	PRM		II	<a href="#">&gt;&gt; 631085</a>
24	4000	3550	PRM		II	<a href="#">&gt;&gt; 631092</a>

### COMPACT LED EVO P IP65 32W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Index
32	3000	3550	OPAL		II	<a href="#">&gt;&gt; 631269</a>
32	4000	3800	OPAL		II	<a href="#">&gt;&gt; 631276</a>
32	3000	4250	PRM		II	<a href="#">&gt;&gt; 631283</a>
32	4000	4550	PRM	yes	II	<a href="#">&gt;&gt; 620805</a>
32	4000	4550	PRM		II	<a href="#">&gt;&gt; 631290</a>

### COMPACT LED EVO P IP65 42W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Index
42	3000	4450	OPAL		II	<a href="#">&gt;&gt; 631146</a>
42	4000	4800	OPAL		II	<a href="#">&gt;&gt; 631153</a>
42	3000	5350	PRM		II	<a href="#">&gt;&gt; 631160</a>
42	4000	5750	PRM		II	<a href="#">&gt;&gt; 631177</a>

### COMPACT LED EVO P IP65 52W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Index
52	3000	5050	OPAL		II	<a href="#">&gt;&gt; 631184</a>
52	4000	5450	OPAL		II	<a href="#">&gt;&gt; 631191</a>
52	3000	6100	PRM		II	<a href="#">&gt;&gt; 631207</a>
52	4000	6550	PRM		II	<a href="#">&gt;&gt; 631214</a>


### COMPACT LED EVO P IP65 60W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	DIMM DALI	Electrical protection class	Index
60	3000	6300	OPAL		I	<a href="#">&gt;&gt; 631221</a>
60	4000	6750	OPAL		I	<a href="#">&gt;&gt; 631238</a>
60	3000	7550	PRM		I	<a href="#">&gt;&gt; 631245</a>
60	4000	8100	PRM		I	<a href="#">&gt;&gt; 631252</a>


# COMPACT LED EVO P IP65

GENERAL CARD

## LUMINOUS INTENSITY DISTRIB. CURVE



COMPACT LED EVO P OPAL




COMPACT LED EVO P PRM

# COMPACT LED EVO P IP65


GENERAL CARD

## ACCESSORIES AVAILABLE


index	Name
<a href="#">998966</a>	Frame steel white structure RAL9016 600x600 SM "well effect"
<a href="#">374845</a>	Frame adapter KG 635x635 WHITE
<a href="#">998973</a>	Frame steel white gloss RAL9016 600x600 SM "well effect"
904349	Safety suspension (modular ceiling)
630033	Plasterboard mounting brackets (4 pcs)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)



Frame adapter KG 635x635 WHITE (374845)



Frame steel white gloss RAL9016 600x600 SM "well effect" (998973)



Safety suspension (modular ceiling) (904349)



Plasterboard mounting brackets (4 pcs) (630033)

Card creation date: 08 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 62/2020