

CALLISTO LED EVO

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK03
Nominal power [W]:	9.00; 15.00
Luminous flux [lm]*:	960 - 1800
Colour temperature [K]:	3000; 4000
SDCM:	4
Energy efficiency class:	E
Material of the body:	galvanized steel
Diffuser material:	glass
Diffuser type:	OPAL
Mounting version:	surface
Dimensions (H/W/T/S) [mm]:	420/103; 420/114;

CHARACTERISTICS

Surface-mounted, round LED luminaire with a very high luminous flux; includes an integrated energy-saving light source LED. Galvanized steel base, powder-coated white; glass diffuser hand-made of multilayer triplex glass which ensures even light distribution. Decorative fitting with an easy-to-clean, simple system mounting the diffuser to the base. Available in four diameters and two finishes: opal and opal mat.

APPLICATION

Surface mounted fitting intended for indoor use in representative rooms and passageways (large conference halls, hotel corridors, studies). Designed for mounting on ceilings and walls. Wide range of diameters and two diffuser versions allow for the same fitting to be used in rooms with different parameters. Well suited to be used as a basic or general interior light source.

CALLISTO LED EVO

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details


CALLISTO LED EVO 420

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions (H/W/T/S) [mm]	Energy efficiency class	Index
9	3000	960	OPAL	420/103	E	>> 065934
9	4000	1040	OPAL	420/103	E	>> 065958
15	4000	1800	OPAL	420/114	E	>> 065996
15	3000	1650	OPAL	420/114	E	>> 065972

CALLISTO LED EVO

GENERAL CARD

LUMINOUS INTENSITY DISTRIB. CURVE



CALLISTO LED

Card creation date: 13 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 395/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl